

FACTOR LED HB 2M 58000LM 840 45D DALI IP66 (434W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	994548
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	434
Luminous flux [lm]*:	58000
Colour temperature [K]:	4000
Colour rendering index:	80
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	D

CHARACTERISTICS

Factor Led HB is the latest generation high bay with high power and high luminous flux. It is characterized not only by very high luminous efficiency, but also by high tightness IP66 and impact resistance IK09. These parameters have been achieved thanks to the use of branded components, a solid housing made of cast aluminum and the use of a passive lamp cooling system, which allows the excess heat generated during lamp operation to be released. The advantage of Factor Led is very quick and simple suspended or surface mounting. The design allows you to hang or mount a lamp consisting of one or two light modules.

APPLICATION

Very good tightness and impact resistance parameters, the ability to work at elevated temperatures - up to 45°C as standard, and an extensive distribution offer give a lot of flexibility in choosing the optimal solution. Factor LED HB will be used and will work great inside industrial halls, warehouses, sports halls, in logistics and exhibition centers and in workshops.


FACTOR LED HB 2M 58000LM 840 45D DALI IP66 (434W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	994548	Impact resistance:	IK09
EAN:	5905963994548	Ingress protection:	IP66
Rated power of the luminaire [W]:	434	Mounting version:	surface-mounted or suspended
Luminous flux [lm]:	58000	Working temperature [°C]:	from -40 to +45
Supply voltage [V]:	220-240	DIMM DALI:	yes
Luminous efficacy [lm/W]:	134	The number of implement units:	2
Energy efficiency class:	D	Dimensions of single box [mm]:	430/410/175
Electrical protection class:	I	Number on the palette [pcs]:	18
Colour temperature [K]:	4000	Net weight [kg]:	9.760
Colour rendering index:	80	Light distribution type:	symmetric
SDCM:	≤ 3	Version:	2 modules
Power factor:	0.98	LED lifespan L70B50 [h]:	156000
Beam angle [°]:	45	LED lifespan L80B20 [h]:	98000
Surge protection [kV]:	6	LED lifespan L90B10 [h]:	47000
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	matrix led	CE certificate:	263/2023
Material of the body:	aluminium	ENEC Certificate:	0404/ENEC/25
Colour of the body:	RAL7016	Environmental Product Declaration (EPD):	816/2025
Dimensions (H/W/T/S) [mm]:	387/397/125	Manual:	Download PDF

LIGHT CURVES




FACTOR LED HB 2M 58000LM 840 45D DALI IP66 (434W)


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
987984	FACTOR LED HB surface mount single 1M
987991	FACTOR LED HB surface mount bracket double 2M



FACTOR LED HB surface mount single 1M (987984)



FACTOR LED HB surface mount bracket double 2M (987991)

Card creation date:10 July 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 263/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl