

FACTOR LED 4M 112000LM 840 30D DALI IP66 (868W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|--------|
| Index: | 993480 |
| Ingress protection: | IP66 |
| Impact resistance: | IK09 |
| Rated power of the luminaire [W]*: | 868 |
| Luminous flux [lm]*: | 112000 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | >80 |
| SDCM: | ≤ 3 |
| Electrical protection class: | I |
| Energy efficiency class: | D |

CHARACTERISTICS

Factor Led is a latest-generation floodlight with a high power output and an impressive luminous flux. It is characterized not only by very high luminous efficiency but also by the highest IP 66 tightness and IK09 impact resistance. These parameters have been achieved thanks to the branded components used, robust housing made of cast aluminum, and the use of a passive cooling system for the lamp, which allows the excess heat generated to be dissipated during lamp operation. The Factor Led has the advantage of very fast and easy installation. The lightweight steel arm is attached to the supporting structure (wall, pole), and then the light modules are plugged in. On a single bracket, the installer can plug in a lamp containing from 1 to 4 such modules.

APPLICATION

Very good sealing and impact resistance parameters, the ability to work in elevated temperatures - up to 45 ° C as standard, and an extensive range of spreads predisposes Factor Led lamps to work in harsh weather conditions. It will find application and perform well both inside industrial halls, warehouses, sports halls, logistics centers, and outdoors - on sports fields, airports, parking lots, and maneuvering areas. It can also illuminate the facades of buildings and elements of external architecture.

DETAILS

FACTOR LED 4M 112000LM 840 30D DALI IP66 (868W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------|---------------------------------------|------------------------------|
| Index: | 993480 | Colour of the body: | RAL7016 |
| EAN: | 5905963993480 | Dimensions (H/W/T/S) [mm]: | 774/425/340 |
| Rated power of the luminaire [W]: | 868 | Impact resistance: | IK09 |
| Luminous flux [lm]: | 112000 | Ingress protection: | IP66 |
| Supply voltage [V]: | 100-277 | Working temperature [°C]: | from -40 to +45 |
| Frequency [Hz]: | 47-63 | DIMM DALI: | yes |
| Luminous efficacy [lm/W]: | 129 | Dimensions of single box [mm]: | 430/810/175 |
| Energy efficiency class: | D | Number on the palette [pcs]: | 18 |
| Electrical protection class: | I | Net weight [kg]: | 21.840 |
| Colour temperature [K]: | 4000 | Version: | 4 modules |
| Colour rendering index: | >80 | LED lifespan L70B50 [h]: | 156000 |
| SDCM: | ≤ 3 | LED lifespan L80B20 [h]: | 98000 |
| Power factor: | 0.97 | LED lifespan L90B10 [h]: | 47000 |
| Beam angle [°]: | 30 | Warranty [years]: | 5 |
| Surge protection [kV]: | 6 | CE certificate: | 262/2023 |
| Diffuser material: | PC | Manual: | Download PDF |
| Material of the body: | aluminium | | |

LIGHT CURVES



Card creation date: 27 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 262/2023

LENA
LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl