

NECTRA LED IP44 20W 3000K BIAŁY

DETAILED CARD



TECHNICAL PARAMETERS

Index:	059384
Ingress protection:	IP44/20
Nominal power [W]:	20
Luminous flux [lm]*:	2000
Colour temperature [K]:	3000
Colour rendering index:	>80
Energy efficiency class:	A+
Material of the body:	PC, aluminium
Diffuser type:	OPAL

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation. Design for both solid and modular ceilings.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings. Available in three power versions and two colour options


NECTRA LED IP44 20W 3000K BIAŁY

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	20	Net weight [kg]:	0.530
Luminous flux [lm]:	2000	CE certificate:	95/2017
Energy efficiency class:	A+	Index:	059384
Electrical protection class:	II	Category type:	downlights
Colour temperature [K]:	3000	Warranty [years]:	5
Colour rendering index:	>80	ETIM class:	EC002892
Diffuser type:	OPAL	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	PC, aluminium	LED lifespan L70B50 [h]:	35000
Dimensions (H/W/T/S) [mm]:	ø222/70	LED lifespan L80B20 [h]:	22000
Mounting dimensions [mm]:	195	LED lifespan L90B10 [h]:	11000
Impact resistance:	IK08	Manual:	Download PDF
Ingress protection:	IP44/20	PZH certificate:	HK/K/1055/06/2017

LIGHT CURVES



NECTRA LED IP44 20W 3000K BIAŁY

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
059735	Round surface casing white NECTRA LED IP44 15W. NECTRA LED 12W
059759	Round surface casing white NECTRA LED IP44 20W. 25W. NECTRA LED 18W
059841	Round surface casing white NECTRA LED IP44 5W. NECTRA LED 5W. 7W, FRAGA LED 11W
059995	NECTRA LED IP44 20W / 25W SURFACE CASEING PC (ø220 / 70)
060922	Round surface casing white NECTRA LED IP44 9W. NECTRA LED 7W, FRAGA 11W



Round surface casing white NECTRA LED IP44 15W. NECTRA LED 12W (059735)



Round surface casing white NECTRA LED IP44 20W. 25W. NECTRA LED 18W (059759)



Round surface casing white NECTRA LED IP44 5W. NECTRA LED 5W. 7W, FRAGA LED 11W (059841)



NECTRA LED IP44 20W / 25W SURFACE CASEING PC (ø220 / 70) (059995)



Round surface casing white NECTRA LED IP44 9W. NECTRA LED 7W, FRAGA 11W (060922)

Card creation date: 06 December 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 95/2017