NECTRA LED IP44 20W 4000K BIAŁY

DETAILED CARD



TECHNICAL PARAMETERS

Index:	059391
Ingress protection:	IP44/20
Nominal power [W]:	20
Luminous flux [lm]*:	2150
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	A+
Material of the body:	PC, aluminium
Diffuser type:	OPAL

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation. Design for both solid and modular ceilings.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings. Available in three power versions and two colour options




NECTRA LED IP44 20W 4000K BIAŁY

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	20	Net weight [kg]:	0.530
Luminous flux [lm]:	2150	CE certificate:	<u>95/2017</u>
Energy efficiency class:	A+	Index:	059391
Electrical protection class:	Ш	Category type:	downlights
Colour temperature [K]:	4000	Warranty [years]:	5
Colour rendering index:	>80	ETIM class:	EC002892
Diffuser type:	OPAL	Photobiological safety:	Risk Group 1 (no photobiological
Material of the body:	PC, aluminium		hazard under normal behavioral limitation)
Dimensions (H/W/T/S) [mm]:	ø222/70	LED lifespan L70B50 [h]:	35000
Mounting dimensions [mm]:	195	LED lifespan L80B20 [h]:	22000
Impact resistance:	IK08	LED lifespan L90B10 [h]:	11000
Ingress protection:	IP44/20	Manual:	Download PDF
	-	PZH certificate:	<u>HK/K/1055/06/2017</u>

LIGHT CURVES



DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
059735	Round surface casing white NECTRA LED IP44 15W. NECTRA LED 12W
059759	Round surface casing white NECTRA LED IP44 20W. 25W. NECTRA LED 18W
059841	Round surface casing white NECTRA LED IP44 5W. NECTRA LED 5W. 7W, FRAGA LED 11W
059995	NECTRA LED IP44 20W / 25W SURFACE CASEING PC (ø220 / 70)
060922	Round surface casing white NECTRA LED IP44 9W. NECTRA LED 7W, FRAGA 11W








Round surface casing white NECTRA LED IP44 5W. NECTRA LED 5W. 7W, FRAGA LED 11W (059841)




Round surface casing white NECTRA LED IP44 15W. NECTRA LED 12W (059735)

Round surface casing white NECTRA LED IP44 9W. NECTRA LED 7W, FRAGA 11W (060922)

Round surface casing white NECTRA LED IP44 20W. 25W. NECTRA LED 18W (059759)



Certificate CE - Nr: 95/2017





The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

A This product is a subject to electric and electronic waste equipment regulations (WEEE).

