


ALTEZZO A 150 1200MM 2100LM 840 IP65 RAL7016 21W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	413148
Ingress protection:	IP65
Impact resistance:	IK08
Nominal power [W]:	20.70
Luminous flux [lm]*:	2100
Colour temperature [K]:	4000
Material of the body:	aluminium
Colour of the body:	RAL7016
Diffuser type:	transparent
Beam angle [°]:	110

CHARACTERISTICS

A family of outdoor lamps with a modern design. The decorative, openwork housing gives the luminaire a lightweight appearance while providing an interesting distribution of accent light. The compact (150mm x 150mm), square-shaped lamp profile is impact-resistant (IK08 or IK09). It is made of aluminium in graphite (RAL 7016). The light module consists of long-life LEDs with a durable polycarbonate aperture. The lamp will provide energy-efficient lighting and safety for users of outdoor areas.

APPLICATION

They are designed for outdoor use. The high tightness of the lamps allows them to be used in harsh weather conditions. They can operate in very low and high temperatures. They will work well in parks and gardens to illuminate small architecture.

ALTEZZO A 150 1200MM 2100LM 840 IP65 RAL7016 21W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	413148	Colour of the body:	RAL7016
EAN:	5905963413148	Dimensions (H/W/T/S) [mm]:	150/150/1200
Light source:	LED	Mounting dimensions [mm]:	75/75 - 90/90
Nominal power [W]:	20.70	Impact resistance:	IK08
Rated power of the luminaire [W]:	21	Ingress protection:	IP65
Supply voltage [V]:	220 - 240	Mounting version:	on a foundation
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -25 to +50
Luminous flux [lm]:	2100	Net weight [kg]:	5.800
Luminous efficacy [lm/W]:	102	Category type:	Park and city lighting
Energy efficiency class:	E	AC voltage range [V]:	90 - 264
Electrical protection class:	I	LED lifespan L70B50 [h]:	174000
Colour temperature [K]:	4000	LED lifespan L80B20 [h]:	110000
Colour rendering index:	>80	LED lifespan L90B10 [h]:	53000
SDCM:	≤ 3	Light distribution type:	general
Beam angle [°]:	110	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Surge protection [kV]:	2	CE certificate:	179/2023
Diffuser type:	transparent	Manual:	Download PDF
Material of the body:	aluminium		

Card creation date: 29 May 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 179/2023