
# MESSAGGIO 1261 MM 2700 LM 840 IP20 I CL. DALI 57 W RAL5025 RAL4011

**DETAILED CARD** 





## **TECHNICAL PARAMETERS**

Index:	57	9189

**Light source:** LED

Rated power [W] - range: 57

Luminous flux of the luminaire [lm] - 2700

range:

**Supply voltage [V]:** 220 - 240

**Frequency [Hz]:** 50 - 60

Electrical protection class:

Colour temperature [K]: 4000

Ingress protection: IP20

**Diffuser material:** PC

#### **CHARACTERISTICS**

The Messaggio collection, designed by Dorota Koziara, includes pendant lamps with a minimalist form. They can come in all RAL colors, including a multicolor version, where the outside of the housing and the inside of the lamp have different colors. In this way, Messaggio provides unlimited design possibilities.

Thanks to the possibility of adjusting the length of the pendants from the Messaggio lamps, surprising light compositions can be created. Versions with DALI control allow you to change the value of the light output, which further enhances the decorative effect. The milky lampshade is made of PC, while the housing is made of solid yet visually delicate steel, which ensures the durability of the product.

### **APPLICATION**

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.



# MESSAGGIO 1261 MM 2700 LM 840 IP20 I CL. DALI 57 W RAL5025 RAL4011

**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

	==0.00
Index:	579189
EAN:	5905963579189
Light source:	LED
Rated power [W] - range:	57
Rated power of the luminaire [W]:	57
Luminous flux of the luminaire [lm] - range:	2700
Luminous flux [lm]:	2700
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous efficacy [Im/W]:	47
Electrical protection class:	1
Colour temperature [K]:	4000
SDCM:	3
LED lifespan L70B50 [h]:	99000
LED lifespan L80B20 [h]:	63000
LED lifespan L90B10 [h]:	31000
Beam angle [°]:	116 x 58
Light distribution type:	open space
Diffuser material:	PC

Diffuser type:	OPAL
Diffuser colour:	milky
Material of the body:	Steel
Colour of the body:	RAL5025/4011
Dimensions (H/W/T/S) [mm]:	1230/1261/80
Mounting dimensions [mm]:	340
Ingress protection:	IP20
Mounting version:	suspended
Working temperature [°C]:	from -25 to +35
Diode PCB material:	aluminium
DIMM DALI:	yes
Control:	yes
Net weight [kg]:	4
Warranty [years]:	5
Category type:	decorative fixtures
CE certificate:	207/2023
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 14 November 2025



