


MESSAGGIO 1541 MM 4300 LM 840 IP20 I CL. DALI 64 W RAL2004 RAL4003

DETAILED CARD



TECHNICAL PARAMETERS

Index:	579028
Light source:	LED
Rated power [W] - range:	64
Luminous flux of the luminaire [lm] - range:	4300
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Electrical protection class:	I
Colour temperature [K]:	4000
Ingress protection:	IP20
Diffuser material:	PC

CHARACTERISTICS

The Messaggio collection, designed by Dorota Koziara, includes pendant lamps with a minimalist form. They can come in all RAL colors, including a multicolor version, where the outside of the housing and the inside of the lamp have different colors. In this way, Messaggio provides unlimited design possibilities.

Thanks to the possibility of adjusting the length of the pendants from the Messaggio lamps, surprising light compositions can be created. Versions with DALI control allow you to change the value of the light output, which further enhances the decorative effect. The milky lampshade is made of PC, while the housing is made of solid yet visually delicate steel, which ensures the durability of the product.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO 1541 MM 4300 LM 840 IP20 I CL. DALI 64 W RAL2004 RAL4003

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	579028	Diffuser type:	OPAL
Rated power [W] - range:	64	Colour of the body:	RAL2004/4003
EAN:	5905963579028	Diffuser colour:	milky
Luminous flux of the luminaire [lm] - range:	4300	Material of the body:	Steel
Light source:	LED	Dimensions (H/W/T/S) [mm]:	1230/1541/80
Rated power of the luminaire [W]:	64	Mounting dimensions [mm]:	340
Luminous flux [lm]:	4300	Ingress protection:	IP20
Supply voltage [V]:	220 - 240	Mounting version:	suspended
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -25 to +35
Colour temperature [K]:	4000	DIMM DALI:	yes
Luminous efficacy [lm/W]:	67	Diode PCB material:	aluminium
Electrical protection class:	I	Control:	yes
SDCM:	≤ 3	Net weight [kg]:	4.870
LED lifespan L70B50 [h]:	99000	Warranty [years]:	5
LED lifespan L80B20 [h]:	63000	Category type:	architectural
LED lifespan L90B10 [h]:	31000	CE certificate:	207/2023
Beam angle [°]:	116 x 58	Manual:	Download PDF
Light distribution type:	open space	Plik LDT:	Download
Diffuser material:	PC		

Card creation date:14 June 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 207/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl