MESSAGGIO BRACKET 1261 MM 2300 - 3950 LM 840 IP20 I CL. 33 - 57 W RAL2004 RAL4003

DETAILED CARD



TECHNICAL PARAMETERS

Rated power [W] - range:	33 - 57
Luminous flux of the luminaire [lm] - range:	2300 - 3950
Luminous efficacy [lm/W]:	69
Electrical protection class:	I
Colour temperature [K]:	4000
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Wall lamps from the Messaggio collection, available in a variety of colors and sizes, can create spectacular light and decorative compositions, designed according to the architect's individual concepts. The LED modules used in the lamps ensure a high level of energy efficiency. The steel, solid, yet visually delicate housing can be painted in the interior and exterior parts in two different RAL colors. The milky lampshade is made of impact-resistant polycarbonate.

Messaggio wall lamps also come in a version with DALI control, which allows you to adjust the value of the luminous flux.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO BRACKET 1261 MM 2300 - 3950 LM 840 IP20 I CL. 33 - 57 W RAL2004 RAL4003

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	579127	**Diffuser type:**	OPAL
EAN:	5905963579127	**Material of the body:**	Steel
Rated power [W] - range:	33 - 57	**Colour of the body:**	RAL2004/4003
Luminous flux of the luminaire [lm] - range:	2300 - 3950	**Dimensions (H/W/T/S) [mm]:**	128/1261/106
Supply voltage [V]:	220 - 240	**Mounting dimensions [mm]:**	340
Frequency [Hz]:	50 - 60	**Ingress protection:**	IP20
Luminous efficacy [lm/W]:	69	**Working temperature [°C]:**	from -25 to +35
Electrical protection class:	I	**Diode PCB material:**	aluminium
Colour temperature [K]:	4000	**Net weight [kg]:**	4.900
SDCM:	3	**Warranty [years]:**	5
LED lifespan L70B50 [h]:	99000	**Category type:**	decorative fixtures
LED lifespan L80B10 [h]:	63000	**Category of application:**	architectural
LED lifespan L90B10 [h]:	31000	**CE certificate:**	208/2023
Beam angle [°]:	116 x 58	**Manual:**	Download PDF
Light distribution type:	open space	**Plik LDT:**	Download
Diffuser material:	PC		

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 208/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl