

# MESSAGGIO STANDING 1246 MM 1300 LM 840 IP20 I CL. DALI SWITCH 23 W RAL8029 RAL1035

DETAILED CARD



## TECHNICAL PARAMETERS

Light source:	LED
Rated power of the luminaire [W]*:	23
Luminous flux [lm]*:	1300
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	57
Electrical protection class:	I
Colour temperature [K]:	4000
LED lifespan L70B50 [h]:	99000
LED lifespan L80B20 [h]:	63000
LED lifespan L90B10 [h]:	31000

## CHARACTERISTICS

The Messaggio collection, designed by Dorota Koziara, includes standing lamps - the first of their kind in the brand's portfolio. Their minimalist form and the option of color personalization provide a wide range of arrangement possibilities. Lamps based on LED module technology, provide a high level of energy efficiency. The steel, solid yet visually delicate housing can be painted in the inner and outer parts in two different RAL colors. The milky lampshade is made of impact-resistant polycarbonate.

Messaggio standing lamps are available with DALI control, which allows to adjust the value of the luminous flux.

## APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions that will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

# MESSAGGIO STANDING 1246 MM 1300 LM 840 IP20 I CL. DALI SWITCH 23 W RAL8029 RAL1035

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	579295	<b>Diffuser colour:</b>	milky
<b>EAN:</b>	5905963579295	<b>Material of the body:</b>	Steel
<b>Light source:</b>	LED	<b>Colour of the body:</b>	RAL8029/1035
<b>Rated power of the luminaire [W]:</b>	23	<b>Dimensions (H/W/T/S) [mm]:</b>	280/1246
<b>Luminous flux [lm]:</b>	1300	<b>Ingress protection:</b>	IP20
<b>Supply voltage [V]:</b>	220 - 240	<b>Mounting version:</b>	Stojąca
<b>Frequency [Hz]:</b>	50 - 60	<b>Working temperature [°C]:</b>	from -25 to +35
<b>Luminous efficacy [lm/W]:</b>	57	<b>Diode PCB material:</b>	aluminium
<b>Electrical protection class:</b>	I	<b>DIMM DALI:</b>	1
<b>Colour temperature [K]:</b>	4000	<b>Control:</b>	yes
<b>SDCM:</b>	≤ 3	<b>Cable length [m]:</b>	3
<b>LED lifespan L70B50 [h]:</b>	99000	<b>Net weight [kg]:</b>	5.760
<b>LED lifespan L80B20 [h]:</b>	63000	<b>Warranty [years]:</b>	5
<b>LED lifespan L90B10 [h]:</b>	31000	<b>Category type:</b>	architectural
<b>Beam angle [°]:</b>	116 x 58	<b>Category of application:</b>	architectural
<b>Light distribution type:</b>	open space	<b>CE certificate:</b>	<a href="#">212/2023</a>
<b>Diffuser material:</b>	PC	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Diffuser type:</b>	OPAL		

Card creation date: 18 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 212/2023