MESSAGGIO STANDING 1246 MM 1400 LM 840 IP20 I CL. DALI SWITCH 23 W RAL5025 RAL4011

DETAILED CARD





TECHNICAL PARAMETERS

Light source:	LED
Rated power of the luminaire [W]*:	23
Luminous flux [lm]*:	1400
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	61
Electrical protection class:	1
Colour temperature [K]:	4000
LED lifespan L70B50 [h]:	99000
LED lifespan L80B20 [h]:	63000
LED lifespan L90B10 [h]:	31000

CHARACTERISTICS

The Messaggio collection, designed by Dorota Koziara, includes standing lamps the first of their kind in the brand's portfolio. Their minimalist form and the option of color personalization provide a wide range of arrangement possibilities. Lamps based on LED module technology, provide a high level of energy efficiency. The steel, solid yet visually delicate housing can be painted in the inner and outer parts in two different RAL colors. The milky lampshade is made of impact-resistant polycarbonate.

Messaggio standing lamps are available with DALI control, which allows to adjust the value of the luminous flux.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions that will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.



MESSAGGIO STANDING 1246 MM 1400 LM 840 IP20 I CL. DALI SWITCH 23 W RAL5025 RAL4011

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	579158
EAN:	5905963579158
Light source:	LED
Rated power of the luminaire [W]:	23
Luminous flux [Im]:	1400
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	61
Electrical protection class:	1
Colour temperature [K]:	4000
SDCM:	3
LED lifespan L70B50 [h]:	99000
LED lifespan L80B20 [h]:	63000
LED lifespan L90B10 [h]:	31000
Beam angle [°]:	116 x 58
Light distribution type:	open space
Diffuser material:	PC
Diffuser type:	OPAL

_	
Diffuser colour:	milky
Material of the body:	Steel
Colour of the body:	RAL5025/4011
Dimensions (H/W/T/S) [mm]:	280/1246
Ingress protection:	IP20
Mounting version:	standing
Working temperature [°C]:	from -25 to +35
Diode PCB material:	aluminium
DIMM DALI:	yes
Control:	yes
Cable length [m]:	3
Net weight [kg]:	5.760
Warranty [years]:	5
Category type:	decorative fixtures
Category of application:	architectural
CE certificate:	212/2023
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 18 July 2023



