MESSAGGIO STANDING 1246 MM 1900 LM 840 IP20 I CL. DALI SWITCH 23 W RAL2004 RAL4003

DETAILED CARD





TECHNICAL PARAMETERS

| LED |
|---------|
| 23 |
| 1900 |
| 50 - 60 |
| 83 |
| 1 |
| 4000 |
| 99000 |
| 63000 |
| 31000 |
| |

CHARACTERISTICS

The Messaggio collection, designed by Dorota Koziara, includes standing lamps the first of their kind in the brand's portfolio. Their minimalist form and the option of color personalization provide a wide range of arrangement possibilities. Lamps based on LED module technology, provide a high level of energy efficiency. The steel, solid yet visually delicate housing can be painted in the inner and outer parts in two different RAL colors. The milky lampshade is made of impact-resistant polycarbonate.

Messaggio standing lamps are available with DALI control, which allows to adjust the value of the luminous flux.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions that will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.



MESSAGGIO STANDING 1246 MM 1900 LM 840 IP20 I CL. DALI SWITCH 23 W RAL2004 RAL4003

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| Index: | 579011 |
|-----------------------------------|---------------|
| EAN: | 5905963579011 |
| Light source: | LED |
| Rated power of the luminaire [W]: | 23 |
| Luminous flux [Im]: | 1900 |
| Supply voltage [V]: | 220 - 240 |
| Frequency [Hz]: | 50 - 60 |
| Luminous efficacy [lm/W]: | 83 |
| Electrical protection class: | 1 |
| Colour temperature [K]: | 4000 |
| SDCM: | 3 |
| LED lifespan L70B50 [h]: | 99000 |
| LED lifespan L80B20 [h]: | 63000 |
| LED lifespan L90B10 [h]: | 31000 |
| Beam angle [°]: | 116 x 58 |
| Light distribution type: | open space |
| Diffuser material: | PC |
| Diffuser type: | OPAL |

| Diffuser colour: | milky |
|----------------------------|---------------------|
| Material of the body: | Steel |
| Colour of the body: | RAL2004/4003 |
| Dimensions (H/W/T/S) [mm]: | 280/1246 |
| Ingress protection: | IP20 |
| Mounting version: | standing |
| Working temperature [°C]: | from -25 to +35 |
| Diode PCB material: | aluminium |
| DIMM DALI: | yes |
| Control: | yes |
| Cable length [m]: | 3 |
| Net weight [kg]: | 5.760 |
| Warranty [years]: | 5 |
| Category type: | decorative fixtures |
| Category of application: | architectural |
| CE certificate: | 212/2023 |
| Manual: | Download PDF |
| Plik LDT: | Download |

Card creation date: 18 July 2023



