

MESSAGGIO STANDING 1246 MM 1900 LM 840 IP20 I CL. DALI SWITCH 23 W RAL2004 RAL4003

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED; moduł LED
Rated power of the luminaire [W]*:	23
Luminous flux [lm]*:	max 4500
Frequency [Hz]:	50 - 60; 50-60
Electrical protection class:	I
Colour temperature [K]:	2700; 3000; 4000
LED lifespan L70B50 [h]:	99000
LED lifespan L80B20 [h]:	63000
LED lifespan L90B10 [h]:	31000

CHARACTERISTICS

The Messaggio collection, designed by Dorota Koziara, includes standing lamps - the first of their kind in the brand's portfolio. Their minimalist form and the option of color personalization provide a wide range of arrangement possibilities. Lamps based on LED module technology, provide a high level of energy efficiency. The steel, solid yet visually delicate housing can be painted in the inner and outer parts in two different RAL colors. The milky lampshade is made of impact-resistant polycarbonate.

Messaggio standing lamps are available with DALI control, which allows to adjust the value of the luminous flux.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions that will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO STANDING 1246 MM 1900 LM 840 IP20 I CL.

DALI SWITCH 23 W RAL2004 RAL4003

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	x	Diffuser colour:	mleczny
EAN:	x	Material of the body:	stal
Light source:	LED; moduł LED	Colour of the body:	max czarny
Rated power of the luminaire [W]:	23	Dimensions (H/W/T/S) [mm]:	280/1246; 300/1807
Luminous flux [lm]:	max 4500	Ingress protection:	IP20
Supply voltage [V]:	220 - 240	Mounting version:	Stojąca
Frequency [Hz]:	50 - 60; 50-60	Working temperature [°C]:	od -25 do +35
Electrical protection class:	I	Diode PCB material:	aluminium
Colour temperature [K]:	2700; 3000; 4000	DIMM DALI:	yes
SDCM:	≤ 3	Control:	tak
LED lifespan L70B50 [h]:	99000	Cable length [m]:	3
LED lifespan L80B20 [h]:	63000	Net weight [kg]:	5.760; 7.800
LED lifespan L90B10 [h]:	31000	Warranty [years]:	5
Beam angle [°]:	116 x 58	Category type:	architectural
Light distribution type:	open space	Category of application:	architectural
Diffuser material:	PC	CE certificate:	212/2023
Diffuser type:	OPAL	Manual:	Download PDF