

# MESSAGGIO STANDING 1807 MM 2500 LM 840 IP20 I CL. DALI SWITCH 44 W RAL8029 RAL1035

DETAILED CARD



## TECHNICAL PARAMETERS

Light source:	LED
Rated power of the luminaire [W]*:	44
Luminous flux [lm]*:	1850
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	42
Electrical protection class:	I
Colour temperature [K]:	4000
LED lifespan L70B50 [h]:	99000
LED lifespan L80B20 [h]:	63000
LED lifespan L90B10 [h]:	31000

## CHARACTERISTICS

The Messaggio collection, designed by Dorota Koziara, includes standing lamps - the first of their kind in the brand's portfolio. Their minimalist form and the option of color personalization provide a wide range of arrangement possibilities. Lamps based on LED module technology, provide a high level of energy efficiency. The steel, solid yet visually delicate housing can be painted in the inner and outer parts in two different RAL colors. The milky lampshade is made of impact-resistant polycarbonate.

Messaggio standing lamps are available with DALI control, which allows to adjust the value of the luminous flux.

## APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions that will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

# MESSAGGIO STANDING 1807 MM 2500 LM 840 IP20 I CL. DALI SWITCH 44 W RAL8029 RAL1035

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	579288	Diffuser colour:	milky
EAN:	5905963579288	Material of the body:	Steel
Light source:	LED	Colour of the body:	RAL8029/1035
Rated power of the luminaire [W]:	44	Dimensions (H/W/T/S) [mm]:	300/1807
Luminous flux [lm]:	1850	Ingress protection:	IP20
Supply voltage [V]:	220 - 240	Mounting version:	Stojąca
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -25 to +35
Luminous efficacy [lm/W]:	42	Diode PCB material:	aluminium
Electrical protection class:	I	DIMM DALI:	yes
Colour temperature [K]:	4000	Control:	yes
SDCM:	≤ 3	Cable length [m]:	3
LED lifespan L70B50 [h]:	99000	Net weight [kg]:	7.800
LED lifespan L80B20 [h]:	63000	Warranty [years]:	5
LED lifespan L90B10 [h]:	31000	Category type:	decorative fixtures
Beam angle [°]:	116 x 58	Category of application:	architectural
Light distribution type:	open space	CE certificate:	<a href="#">212/2023</a>
Diffuser material:	PC	Manual:	<a href="#">Download PDF</a>
Diffuser type:	OPAL	Plik LDT:	<a href="#">Download</a>