# MESSAGGIO BRACKET XS 59 LM 840 IP20 I CL. DALI 2 W RAL2004 RAL4003

DETAILED CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Rated power of the luminaire [W]*:** | 2 |
| **Luminous flux [lm]*:** | 59 |
| **Electrical protection class:** | I |
| **Diffuser material:** | PC |
| **Diffuser type:** | OPAL |
| **Material of the body:** | Steel |
| **Colour of the body:** | RAL2004/4003 |
| **Dimensions (H/W/T/S) [mm]:** | 200/130/140 |

## CHARACTERISTICS

Messaggio small wall sconces surprise with their minimalist form and color personalization option. The lamps can be painted in any shade from the RAL palette and create phenomenal light decorations, designed according to the architect's individual concepts. The lamp housing is made of sturdy but visually delicate steel, while the lampshade is made of milky PC.

Messaggio wall lamps also come in a version with DALI control, which allows you to adjust the value of the light output.

## APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

# MESSAGGIO BRACKET XS 59 LM 840 IP20 I CL. DALI 2 W RAL2004 RAL4003

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | |
|---|---|
| **Index:** | 579073 |
| **EAN:** | 5905963579073 |
| **Light source:** | LED |
| **Rated power of the luminaire [W]:** | 2 |
| **Luminous flux [lm]:** | 59 |
| **Supply voltage [V]:** | 220 - 240 |
| **Frequency [Hz]:** | 50 - 60 |
| **Electrical protection class:** | I |
| **Colour temperature [K]:** | 4000 |
| **SDCM:** | 3 |
| **LED lifespan L70B50 [h]:** | 108000 |
| **LED lifespan L80B10 [h]:** | 108000 |
| **LED lifespan L90B10 [h]:** | 108000 |
| **Diffuser material:** | PC |
| **Diffuser type:** | OPAL |

| | |
|---|---|
| **Diffuser colour:** | milky |
| **Material of the body:** | Steel |
| **Colour of the body:** | RAL2004/4003 |
| **Dimensions (H/W/T/S) [mm]:** | 200/130/140 |
| **Ingress protection:** | IP20 |
| **Working temperature [°C]:** | from -25 to +35 |
| **DIMM DALI:** | yes |
| **Warranty [years]:** | 5 |
| **Category type:** | decorative fixtures |
| **Category of application:** | architectural |
| **CE certificate:** | 209/2023 |
| **Manual:** | Download PDF |
| **ISO Certificates:** | 9001:2015, 14001:2015, 45001:2018, 50001:2018 |
| **Plik LDT:** | Download |

Card creation date: 22 June 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 209/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl