MESSAGGIO BRACKET XS 59 LM 840 IP20 I CL. DALI 2 W RAL5025 RAL4011

DETAILED CARD





TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	2	
Luminous flux [lm]*:	59	
Electrical protection class:	I	
Diffuser material:	PC	
Diffuser type:	OPAL	
Material of the body:	Steel	
Colour of the body:	RAL5025/4011	
Dimensions (H/W/T/S) [mm]: 200/130/140		

CHARACTERISTICS

Messaggio small wall sconces surprise with their minimalist form and color personalization option. The lamps can be painted in any shade from the RAL palette and create phenomenal light decorations, designed according to the architect's individual concepts. The lamp housing is made of sturdy but visually delicate steel, while the lampshade is made of milky PC.

Messaggio wall lamps also come in a version with DALI control, which allows you to adjust the value of the light output.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.



MESSAGGIO BRACKET XS 59 LM 840 IP20 I CL. DALI 2 W RAL5025 RAL4011

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	579219	Diffuser type:	OPAL
EAN:	5905963579219	Diffuser colour:	milky
Light source:	LED	Material of the body:	Steel
Rated power of the luminaire [W]:	2	Colour of the body:	RAL5025/4011
Luminous flux [lm]:	59	Dimensions (H/W/T/S) [mm]:	200/130/140
Supply voltage [V]:	220 - 240	Ingress protection:	IP20
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -25 to +35
Electrical protection class:	1	DIMM DALI:	yes
Colour temperature [K]:	4000	Warranty [years]:	5
SDCM:	≤ 3	Category type:	decorative fixtures
LED lifespan L70B50 [h]:	99000	Category of application:	architectural
LED lifespan L80B20 [h]:	63000	CE certificate:	<u>209/2023</u>
LED lifespan L90B10 [h]:	31000	Manual:	Download PDF
Diffuser material:	PC	Plik LDT:	Download

Card creation date: 11 April 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

CE Certificate CE - Nr: 209/2023

This product is a subject to electric and electronic waste equipment regulations (WEEE).



A