

# TERRANO S/R 630X48MM 1200LM 840 I CL. WHITE 60D (9W)

DETAILED CARD



## TECHNICAL PARAMETERS

|                                    |                     |
|------------------------------------|---------------------|
| Index:                             | 577628              |
| Rated power of the luminaire [W]*: | 9                   |
| Luminous flux [lm]*:               | 1200                |
| Luminous efficacy [lm/W]:          | 133                 |
| Colour temperature [K]:            | 4000                |
| Energy efficiency class:           | G                   |
| Electrical protection class:       | I                   |
| Beam angle [°]:                    | 60                  |
| Material of the body:              | powder coated steel |
| Diffuser material:                 | PC                  |

## CHARACTERISTICS

Thanks to the use of the latest generation of LED modules, the new Terrano S/R linear luminaire is characterised by energy efficiency and outstanding technical performance. Equipped with a focusing lens, Terrano S/R luminaires are visually friendly and effectively reduce glare (UGR of 12-19). Mounted in a trunking system, they are available in two colour temperatures of 3000 K and 4000 K and two colour versions: white and black. The 630mm-long version allows 360° rotation around its axis and 45° rotation of the light system. The 1180mm version allows the light system to rotate 45°. DALI version available on request.

## APPLICATION

Mounting on a trunking system, increases the range of applications for this luminaire and allows for rearrangement by the user, even after installation. The luminaire has an adaptor equipped with mechanical clips which make it easy to plug in, unplug and move the luminaire, while ensuring that the luminaire is securely held in the rail. The luminaires, together with suitably selected rails and components, allow for ceiling or wall mounting. The Terrano S/R luminaire is ideal as a source of light in offices, shops, dressing rooms and passageways.

# TERRANO S/R 630X48MM 1200LM 840 I CL. WHITE 60D (9W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |               |                            |                              |
|-----------------------------------|---------------|----------------------------|------------------------------|
| Index:                            | 577628        | Optics material:           | PC                           |
| Rated power of the luminaire [W]: | 9             | Optics:                    | lens                         |
| EAN:                              | 5905963577628 | Material of the body:      | powder coated steel          |
| Luminous flux [lm]:               | 1200          | Ingress protection:        | IP20                         |
| Light source:                     | LED           | Mounting version:          | track                        |
| Colour temperature [K]:           | 4000          | Working temperature [°C]:  | from -10 to +35              |
| Colour of the body:               | white         | Tilt angle adjustment [°]: | no                           |
| Beam angle [°]:                   | 60            | Net weight [kg]:           | 1.120                        |
| Dimensions (H/W/T/S) [mm]:        | 48/630/85     | Category type:             | louvres                      |
| Luminous efficacy [lm/W]:         | 133           | Light distribution type:   | symmetric                    |
| Energy efficiency class:          | G             | LED lifespan L70B50 [h]:   | 150000                       |
| Electrical protection class:      | I             | LED lifespan L80B20 [h]:   | 100000                       |
| Colour rendering index:           | >80           | LED lifespan L90B10 [h]:   | 50000                        |
| SDCM:                             | ≤ 3           | Warranty [years]:          | 5                            |
| Surge protection [kV]:            | 1             | CE certificate:            | <a href="#">66/2025</a>      |
| Diffuser material:                | PC            | Manual:                    | <a href="#">Download PDF</a> |
| Diffuser type:                    | matrix led    | Plik LDT:                  | <a href="#">Download</a>     |
| Diffuser colour:                  | transparent   |                            |                              |

## LIGHT CURVES

