

CORIA 2 3200LM 300MM DALI I CL. IP44 SUSPENDED MICROPRM WHITE MAT 840 28W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	415463
Ingress protection:	IP40
Impact resistance:	IK03
Rated power [W] - range:	28
Luminous flux of the luminaire [lm] - range:	3200
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Electrical protection class:	I
Material of the body:	aluminium
Colour of the body:	white

CHARACTERISTICS

The Coria 2 LED circular luminaire with integrated energy-efficient LED module is characterised by its high luminous efficacy and uniform light distribution. Its base is made of white or black powder-coated aluminium and its diffuser is made of microprism (300mm diameter version only) or opal plastic. It is ideal for new applications and for replacing traditional fluorescent lamps with energy-efficient LED solutions. Characteristics: colour temperature 3000K, 4000K; CRI>80; LED module life 119,000 hours (L80B20) ta = 25°C; pendant or surface-mounted version.

APPLICATION

The luminaire is designed for indoor use. It is characterised by even light distribution and good surface illumination, which is why it is particularly dedicated as a source of general light in representative rooms and passageways. Thanks to its excellent luminous parameters, the luminaire is ideal for large conference rooms. The luminaire's construction has been adapted for surface-mounted or flush-mounted installation in plasterboard ceilings. Revit files for architectural luminaires are available on request.

CORIA 2 3200LM 300MM DALI I CL. IP44 SUSPENDED MICROPRM WHITE MAT 840 28W

DETAILED CARD


TECHNICAL PARAMETERS TABLE

Index:	415463	Impact resistance:	IK03
EAN:	5905963415463	Ingress protection:	IP40
Light source:	LED	Mounting version:	suspended
Rated power [W] - range:	28	Working temperature [°C]:	from -10 to +35
Supply voltage [V]:	220 - 240	DIMM DALI:	yes
Frequency [Hz]:	50 - 60	Dimensions of single box [mm]:	325/325/90
Luminous flux of the luminaire [lm] - range:	3200	Number on the palette [pcs]:	42
Luminous efficacy [lm/W]:	114	Net weight [kg]:	2.400
Energy efficiency class:	E	Category type:	bulkheads
Electrical protection class:	I	LED lifespan L70B50 [h]:	102340
Colour temperature [K]:	4000	LED lifespan L80B10 [h]:	64800
Color rendering index (Ra) >:	80	LED lifespan L90B10 [h]:	31670
Surge protection [kV]:	1	Light distribution type:	lambertian
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	PRM	CE certificate:	149/2025
Material of the body:	aluminium	Manual:	Download PDF
Colour of the body:	white	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Dimensions (H/W/T/S) [mm]:	300/85	Plik LDT:	Download
Mounting dimensions [mm]:	109/109		

Card creation date: 11 January 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 149/2025