

STRADO LED S 10900LM 740 RM7 IP66 II CL. DALI (84W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	408311
Ingress protection:	IP66
Impact resistance:	IK10
Rated power of the luminaire [W]*:	84
Luminous flux [lm]*:	10900
Colour temperature [K]:	4000
Colour rendering index:	> 70
Electrical protection class:	II
Optics:	RM7
Control:	5-stage power reduction

CHARACTERISTICS

STRADO LED is a new family of LED road luminaires. It uses directional multi-lens matrices, made of PMMA, with each lens having the same optics, ensuring that the luminous characteristics remain constant over time. Components from renowned manufacturers and state-of-the-art LED panels contribute to the very high luminous efficacy achieved at the output of the luminaire - reaching 165 lm/W. The upper part of the body has a separate electrical cavity in the body, which allows for efficient cooling of all power supply components, independently of the light module. The lower surface of the luminaire is finished entirely with toughened glass, providing high aesthetic qualities. The luminaire has an outgoing cable with a quick-release connector, which allows fast, convenient and reliable installation without opening the luminaire. Using standard tools, it is possible to service the luminaire, allowing any component to be replaced without soldering. The body and fixture are made of die-cast aluminium, powder-coated grey, and have a very high IP66 ingress protection rating and IK10 mechanical impact resistance. Standard features: fully programmable DALI driver; available functions for maintaining constant luminous flux during CLO and autonomous 5-step power reduction; NTC protection against accidental overheating of the luminaire; filter to prevent condensation; outgoing cable with quick-connector. Additional options: NEMA, ZHAGA connectors on the top of the luminaire; interfacing with control systems; additional SP10kV protection outside the power supply, on/off power supply without power reduction function; painting in any RAL colour. Certifications: CE, RoHS, ENEC, ENEC+, Zhaga D4i.

APPLICATION

Thanks to the use of dedicated optics, it is possible to illuminate objects such as: highways, expressways, national, provincial, county, municipal, city, neighborhood, area lighting. Optics are also available to illuminate: pedestrian crossings, sidewalks and bicycle paths.

STRADO LED S 10900LM 740 RM7 IP66 II CL. DALI (84W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	408311	Exchangeable source:	yes
Rated power of the luminaire [W]:	84	Material of the body:	powder coated aluminium
EAN:	5905963408311	Colour of the body:	grey
Luminous flux [lm]:	10900	Dimensions (H/W/T/S) [mm]:	385/265/60
ETIM class:	EC000062	Mounting dimensions [mm]:	ø60
Luminous efficacy [lm/W]:	130	Impact resistance:	IK10
Category type:	street lighting	Ingress protection:	IP66
Energy efficiency class:	D	Mounting version:	Top, on pole / Side, on boom
Colour temperature [K]:	4000	Tilt angle adjustment [°]:	-20° to +20°
Version:	S	Lateral surface (SCx) [m2]:	0.018
Colour rendering index:	> 70	Working temperature [°C]:	from -40 to +50
Light source:	LED module	Control:	5-stage power reduction
Electrical protection class:	II	Protection type:	NTC + ESD
Optics:	RM7	Net weight [kg]:	4.440
Supply voltage [V]:	220 - 240	ULOR:	0%
DIMM DALI:	yes	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Frequency [Hz]:	50 - 60	Technical Warranty:	5 with the possibility of extension to 10
SDCM:	≤ 5	ENEC Certificate:	0390/ENEC/24; 0133/ENEC+/24
Power factor:	0.98	CE certificate:	85/2023
Surge protection [kV]:	10	Zhaga-D4i:	ZG415127092023
Diffuser material:	toughened glass	Environmental Product Declaration (EPD):	682/2024
Diffuser type:	transparent	Manual:	Download PDF
Optics material:	PMMA	LED lifespan L95B10 [h]:	100000

LIGHT CURVES



STRADO LED S 10900LM 740 RM7 IP66 II CL. DALI (84W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)



wall holder (galvanized) (314049)



wall holder (grey) (314056)

Card creation date: 06 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 85/2023