

COMPACT LED EVO N 60W 840 OPAL DALI I KL

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Impact resistance:	IK07
Nominal power [W]:	60
Luminous flux [lm]*:	6750
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	E
Material of the body:	ABS
Diffuser material:	PC

CHARACTERISTICS

Compact LED luminaire designed for surface mounting. Equipped with energy-saving LED modules and an evenly highlighted opal or prismatic diffuser, providing low glare (UGR<19)*. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions. The fitting's design is suitable for mounting in 600x600 modular ceilings.

DETAILS

The corridor function makes it possible to adapt the lighting intensity in objects to changing conditions. In practice, it automatically reduces the lamp's luminous flux from 100% to 10%. Automatic mode 10 to 100 (version with RCR Hytronik motion detector) The lamp constantly illuminates at 10% of its luminous flux. When the motion sensor detects movement in the preset detection field, the lamp lights up to 100% luminous flux and remains on for the preset time. After the preset operating time, the lamp switches to energy-saving mode and illuminates 10% of the luminous flux. It is possible to connect an ON/OFF switch to switch the lamp off completely.


COMPACT LED EVO N 60W 840 OPAL DALI I KL

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	629440	Ingress protection:	IP20
EAN:	5905963629440	Mounting version:	surface
Light source:	LED module	Working temperature [°C]:	from -20 to +35
Nominal power [W]:	60	DIMM DALI:	yes
Rated power of the luminaire [W]:	65	Net weight [kg]:	2.800
Supply voltage [V]:	220-240	Category type:	troffers
Frequency [Hz]:	50 - 60	LED lifespan L70B50 [h]:	115000
Luminous flux [lm]:	6750	LED lifespan L80B10 [h]:	72000
Luminous efficacy [lm/W]:	103	LED lifespan L90B10 [h]:	35000
Energy efficiency class:	E	Power factor:	0.98
Electrical protection class:	I	ETIM class:	EC002892
Colour temperature [K]:	4000	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Color rendering index (Ra) >:	80	Warranty [years]:	5
SDCM:	3	CE certificate:	356/2023
Diffuser material:	PC	ENEC Certificate:	PL_BB/J/009/2021/M1
Diffuser type:	OPAL	Environmental Product Declaration (EPD):	944/2026
Material of the body:	ABS	Manual:	Download PDF
Colour of the body:	white	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Dimensions (H/W/T/S) [mm]:	620/620/66	Pliik LDT:	Download
Impact resistance:	IK07		

LIGHT CURVES



COMPACT LED EVO N 60W 840 OPAL DALI I KL

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
630279	Compact - Uchwyt do mocowania natynkowego - specjalny / Holder for surface mounting - special



Compact - Uchwyt do mocowania natynkowego - specjalny / Holder for surface mounting - special (630279)

Card creation date: 28 April 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 356/2023