

# COMPACT LED EVO N 60W 840 PRM DALI I KL

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP20
<b>Impact resistance:</b>	IK07
<b>Nominal power [W]:</b>	60
<b>Luminous flux [lm]*:</b>	8100
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	ABS
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

Compact LED luminaire designed for surface mounting. Equipped with energy-saving LED modules and an evenly highlighted opal or prismatic diffuser, providing low glare (UGR<19)\*. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

## APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions. The fitting's design is suitable for mounting in 600x600 modular ceilings.

# COMPACT LED EVO N 60W 840 PRM DALI I KL

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	60	Working temperature [°C]:	from -20 to +35
Index:	629464	DIMM DALI:	1
Colour temperature [K]:	4000	Net weight [kg]:	2.800
Light source:	LED module	CE certificate:	<a href="#">356/2023</a>
Luminous flux [lm]:	8100	PZH certificate:	<a href="#">B-BK-60212-0070/20 B-BK-60212-0042/20</a>
Diffuser type:	PRM	EAN:	5905963629464
Rated power of the luminaire [W]:	65	Category type:	louvres
Supply voltage [V]:	220-240	LED lifespan L70B50 [h]:	115000
Frequency [Hz]:	50 - 60	LED lifespan L80B20 [h]:	72000
Luminous efficacy [lm/W]:	124	LED lifespan L90B10 [h]:	35000
Energy efficiency class:	D	Warranty [years]:	5
Electrical protection class:	I	Power factor:	0.98
Colour rendering index:	>80	ETIM class:	EC002892
SDCM:	≤ 3	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	PC	Manual:	<a href="#">Download PDF</a>
Material of the body:	ABS	ENEC Certificate:	<a href="#">PL BBJ/009/2021/M1</a>
Colour of the body:	white	Pliik LDT:	<a href="#">Pobierz</a>
Dimensions (H/W/T/S) [mm]:	620/620/66		
Impact resistance:	IK07		
Ingress protection:	IP20		
Mounting version:	surface		

## TECHNICAL DETAILS



COMPACT LED EVO PRM

# COMPACT LED EVO N 60W 840 PRM DALI I KL

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
630279	Compact - Uchwyt do mocowania natynkowego - specjalny / Holder for surface mounting - special



Compact - Uchwyt do mocowania natynkowego - specjalny / Holder for surface mounting - special (630279)

Card creation date: 03 February 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 356/2023