

# COMPACT LED EVO N 8100LM PRM RCR I KL. IP20 620X620 840 (60W) CORRIDOR

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP20
<b>Impact resistance:</b>	IK07
<b>Nominal power [W]:</b>	60
<b>Luminous flux [lm]*:</b>	8100
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	ABS
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

Compact LED luminaire designed for surface mounting. Equipped with energy-saving LED modules and an evenly highlighted opal or prismatic diffuser, providing low glare (UGR<19)\*. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

## APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions. The fitting's design is suitable for mounting in 600x600 modular ceilings.

# COMPACT LED EVO N 8100LM PRM RCR I KL. IP20 620X620 840 (60W) CORRIDOR

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	630156	Mounting version:	surface
Light source:	LED module	Working temperature [°C]:	from -25 to +60
Nominal power [W]:	60	Corridor function:	yes
Rated power of the luminaire [W]:	60	Motion sensor:	yes
Supply voltage [V]:	220-240	DIMM DALI:	yes
Frequency [Hz]:	50 - 60	Net weight [kg]:	2.850
Luminous flux [lm]:	8100	CE certificate:	<a href="#">356/2023</a>
Luminous efficacy [lm/W]:	135	PZH certificate:	<a href="#">B-BK-60212-0070/20 B-BK-60212-0042/20</a>
Energy efficiency class:	D	EAN:	5905963655289
Electrical protection class:	I	Category type:	louvres
Colour temperature [K]:	4000	LED lifespan L70B50 [h]:	115000
Colour rendering index:	>80	LED lifespan L80B20 [h]:	72000
SDCM:	≤ 3	LED lifespan L90B10 [h]:	35000
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	PRM	Power factor:	0.95
Material of the body:	ABS	ETIM class:	EC002892
Colour of the body:	white	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Dimensions (H/W/T/S) [mm]:	620/620/66	Manual:	<a href="#">Download PDF</a>
Impact resistance:	IK07	ENEC Certificate:	<a href="#">PL BBJ/009/2021/M1</a>
Ingress protection:	IP20		

## LIGHT CURVES



# COMPACT LED EVO N 8100LM PRM RCR I KL. IP20 620X620 840 (60W) CORRIDOR

---

DETAILED CARD

## TECHNICAL DETAILS

---



COMPACT LED EVO PRM

# COMPACT LED EVO N 8100LM PRM RCR I KL. IP20 620X620 840 (60W) CORRIDOR

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
630279	Compact - Uchwyt do mocowania natynkowego - specjalny / Holder for surface mounting - special



Compact - Uchwyt do mocowania  
natynkowego - specjalny / Holder for  
surface mounting - special (630279)

Card creation date: 03 February 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 356/2023