

# EXPO LED 3 MINI 2827LM 830 15° BLACK (22W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	836558
<b>Rated power of the luminaire [W]*:</b>	22
<b>Ingress protection:</b>	IP20
<b>Luminous flux [lm]*:</b>	2827
<b>Colour temperature [K]:</b>	3000
<b>Colour rendering index:</b>	>80
<b>Electrical protection class:</b>	I
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	black

## CHARACTERISTICS

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

## APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

# EXPO LED 3 MINI 2827LM 830 15° BLACK (22W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	22	Energy efficiency class:	D
Index:	836558	Electrical protection class:	I
Colour temperature [K]:	3000	Optics material:	aluminium
EAN:	5905963836558	Material of the body:	aluminium
Luminous flux [lm]:	2827	Dimensions (H/W/T/S) [mm]:	86/185
Light source:	LED	Ingress protection:	IP20
Colour rendering index:	>80	Dimensions of single box [mm]:	285/122/122
Beam angle [°]:	15°	Net weight [kg]:	0.810
Supply voltage [V]:	220 - 240	Category type:	spotlight
Colour of the body:	black	LED lifespan L90B10 [h]:	49000
Optics:	reflector	Warranty [years]:	5
Luminous efficacy [lm/W]:	129	Manual:	<a href="#">Download PDF</a>

Card creation date: 12 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr./2023