# EXPO LED 3 MINI 2950LM 840 15° BLACK (22W)

DETAILED CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Index:** | 836619 |
| **Rated power of the luminaire [W]*:** | 22 |
| **Ingress protection:** | IP20 |
| **Luminous flux [lm]*:** | 2950 |
| **Colour temperature [K]:** | 4000 |
| **Color rendering index (Ra) >:** | 80 |
| **Electrical protection class:** | I |
| **Energy efficiency class:** | D |
| **Material of the body:** | aluminium |
| **Colour of the body:** | black |

## CHARACTERISTICS

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

## APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

# EXPO LED 3 MINI 2950LM 840 15° BLACK (22W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | |
|---|---|
| **Index:** | 836619 |
| **EAN:** | 5905963836619 |
| **Light source:** | LED |
| **Rated power of the luminaire [W]:** | 22 |
| **Supply voltage [V]:** | 220 - 240 |
| **Luminous flux [lm]:** | 2950 |
| **Luminous efficacy [lm/W]:** | 134 |
| **Energy efficiency class:** | D |
| **Electrical protection class:** | I |
| **Colour temperature [K]:** | 4000 |
| **Color rendering index (Ra) >:** | 80 |
| **Beam angle [°]:** | 15 |
| **Optics material:** | aluminium |

| | |
|---|---|
| **Optics:** | reflector |
| **Material of the body:** | aluminium |
| **Colour of the body:** | black |
| **Dimensions (H/W/T/S) [mm]:** | 86/185 |
| **Ingress protection:** | IP20 |
| **Dimensions of single box [mm]:** | 285/122/122 |
| **Net weight [kg]:** | 0.810 |
| **Category type:** | spotlight |
| **LED lifespan L90B10 [h]:** | 49000 |
| **Warranty [years]:** | 5 |
| **Manual:** | Download PDF |
| **Plik LDT:** | Download |

Card creation date: 12 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 109/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl