

EXPO LED 3 MINI 2827LM 830 38° BLACK (22W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	836671
Rated power of the luminaire [W]*:	22
Ingress protection:	IP20
Luminous flux [lm]*:	2827
Colour temperature [K]:	3000
Colour rendering index:	>80
Electrical protection class:	I
Energy efficiency class:	D
Material of the body:	aluminium
Colour of the body:	black

CHARACTERISTICS

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

EXPO LED 3 MINI 2827LM 830 38° BLACK (22W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	836671	Optics material:	aluminium
EAN:	5905963836671	Optics:	reflector
Light source:	LED	Material of the body:	aluminium
Rated power of the luminaire [W]:	22	Colour of the body:	black
Supply voltage [V]:	220 - 240	Dimensions (H/W/T/S) [mm]:	86/185
Luminous flux [lm]:	2827	Ingress protection:	IP20
Luminous efficacy [lm/W]:	129	Dimensions of single box [mm]:	285/122/122
Energy efficiency class:	D	Net weight [kg]:	0.810
Electrical protection class:	I	Category type:	spotlight
Colour temperature [K]:	3000	LED lifespan L90B10 [h]:	49000
Colour rendering index:	>80	Warranty [years]:	5
Beam angle [°]:	38°	Manual:	Download PDF

Card creation date: 12 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr./2023