

# EXPO LED 3 MINI 1046LM 930 15° WHITE (9W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	836923
<b>Rated power of the luminaire [W]*:</b>	9
<b>Ingress protection:</b>	IP20
<b>Luminous flux [lm]*:</b>	1046
<b>Colour temperature [K]:</b>	3000
<b>Color rendering index (Ra) &gt;:</b>	90
<b>Electrical protection class:</b>	I
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	white

## CHARACTERISTICS

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

## APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

# EXPO LED 3 MINI 1046LM 930 15° WHITE (9W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	836923	<b>Optics:</b>	reflector
<b>EAN:</b>	5905963836923	<b>Material of the body:</b>	aluminium
<b>Light source:</b>	LED	<b>Colour of the body:</b>	white
<b>Rated power of the luminaire [W]:</b>	9	<b>Dimensions (H/W/T/S) [mm]:</b>	86/185
<b>Supply voltage [V]:</b>	220 - 240	<b>Ingress protection:</b>	IP20
<b>Luminous flux [lm]:</b>	1046	<b>Dimensions of single box [mm]:</b>	285/122/122
<b>Luminous efficacy [lm/W]:</b>	116	<b>Net weight [kg]:</b>	0.810
<b>Energy efficiency class:</b>	E	<b>Category type:</b>	spotlight
<b>Electrical protection class:</b>	I	<b>LED lifespan L90B10 [h]:</b>	64000
<b>Colour temperature [K]:</b>	3000	<b>Warranty [years]:</b>	5
<b>Color rendering index (Ra) &gt;:</b>	90	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Beam angle [°]:</b>	15	<b>Plik LDT:</b>	<a href="#">Download</a>
<b>Optics material:</b>	aluminium		

Card creation date: 12 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: /2023