

EXPO LED 3 MINI 2827LM 830 38° WHITE (22W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	837043
Rated power of the luminaire [W]*:	22
Ingress protection:	IP20
Luminous flux [lm]*:	2827
Colour temperature [K]:	3000
Colour rendering index:	>80
Electrical protection class:	I
Energy efficiency class:	D
Material of the body:	aluminium
Colour of the body:	white

CHARACTERISTICS

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

EXPO LED 3 MINI 2827LM 830 38° WHITE (22W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	837043	Electrical protection class:	I
Rated power of the luminaire [W]:	22	Colour rendering index:	>80
EAN:	5905963837043	Optics material:	aluminium
Colour temperature [K]:	3000	Material of the body:	aluminium
Luminous flux [lm]:	2827	Dimensions (H/W/T/S) [mm]:	86/185
Light source:	LED	Ingress protection:	IP20
Beam angle [°]:	38°	Dimensions of single box [mm]:	285/122/122
Supply voltage [V]:	220 - 240	Net weight [kg]:	0.810
Colour of the body:	white	Category type:	spotlight
Optics:	reflector	LED lifespan L90B10 [h]:	49000
Energy efficiency class:	D	Warranty [years]:	5
Luminous efficacy [lm/W]:	129	Manual:	Download PDF

Card creation date: 12 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr./2023