EXPO LED 3 MINI 1297LM 840 38° WHITE (9W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	837081
Rated power of the luminaire [W]*:	9
Ingress protection:	IP20
Luminous flux [lm]*:	1297
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Electrical protection class:	I
Energy efficiency class:	D
Material of the body:	aluminium
Colour of the body:	white

CHARACTERISTICS

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

EXPO LED 3 MINI 1297LM 840 38° WHITE (9W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	837081
EAN:	5905963837081
Light source:	LED
Rated power of the luminaire [W]:	9
Supply voltage [V]:	220 - 240
Luminous flux [lm]:	1297
Luminous efficacy [lm/W]:	144
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Beam angle [°]:	38
Optics material:	aluminium

Optics:	reflector
Material of the body:	aluminium
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	86/185
Ingress protection:	IP20
Dimensions of single box [mm]:	285/122/122
Net weight [kg]:	0.810
Category type:	spotlight
LED lifespan L90B10 [h]:	64000
Warranty [years]:	5
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 12 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 109/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl