

EXPO LED 3 MINI 2170LM 940 38° WHITE (17W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	837128
Rated power of the luminaire [W]*:	17
Ingress protection:	IP20
Luminous flux [lm]*:	2170
Colour temperature [K]:	4000
Colour rendering index:	>90
Electrical protection class:	I
Energy efficiency class:	D
Material of the body:	aluminium
Colour of the body:	white

CHARACTERISTICS

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

EXPO LED 3 MINI 2170LM 940 38° WHITE (17W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	17	Energy efficiency class:	D
Index:	837128	Electrical protection class:	I
Colour temperature [K]:	4000	Optics material:	aluminium
EAN:	5905963837128	Material of the body:	aluminium
Luminous flux [lm]:	2170	Dimensions (H/W/T/S) [mm]:	86/185
Light source:	LED	Ingress protection:	IP20
Colour rendering index:	>90	Dimensions of single box [mm]:	285/122/122
Beam angle [°]:	38°	Net weight [kg]:	0.810
Supply voltage [V]:	220 - 240	Category type:	spotlight
Colour of the body:	white	LED lifespan L90B10 [h]:	53000
Optics:	reflector	Warranty [years]:	5
Luminous efficacy [lm/W]:	128	Manual:	Download PDF

Card creation date: 12 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr./2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl