

# EXPO LED 3 MINI 2561LM 940 38° WHITE (22W)

DETAILED CARD



## TECHNICAL PARAMETERS

|   |           |
|---|-----------|
| <b>Index:</b>                             | 837135    |
| <b>Rated power of the luminaire [W]*:</b> | 22        |
| <b>Ingress protection:</b>                | IP20      |
| <b>Luminous flux [lm]*:</b>               | 2561      |
| <b>Colour temperature [K]:</b>            | 4000      |
| <b>Colour rendering index:</b>            | >90       |
| <b>Electrical protection class:</b>       | I         |
| <b>Energy efficiency class:</b>           | E         |
| <b>Material of the body:</b>              | aluminium |
| <b>Colour of the body:</b>                | white     |

## CHARACTERISTICS

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

## APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

# EXPO LED 3 MINI 2561LM 940 38° WHITE (22W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |               |                                |                              |
|-----------------------------------|---------------|--------------------------------|------------------------------|
| Rated power of the luminaire [W]: | 22            | Energy efficiency class:       | E                            |
| Index:                            | 837135        | Electrical protection class:   | I                            |
| Colour temperature [K]:           | 4000          | Optics material:               | aluminium                    |
| EAN:                              | 5905963837135 | Material of the body:          | aluminium                    |
| Luminous flux [lm]:               | 2561          | Dimensions (H/W/T/S) [mm]:     | 86/185                       |
| Light source:                     | LED           | Ingress protection:            | IP20                         |
| Colour rendering index:           | >90           | Dimensions of single box [mm]: | 285/122/122                  |
| Beam angle [°]:                   | 38°           | Net weight [kg]:               | 0.810                        |
| Supply voltage [V]:               | 220 - 240     | Category type:                 | spotlight                    |
| Colour of the body:               | white         | LED lifespan L90B10 [h]:       | 49000                        |
| Optics:                           | reflector     | Warranty [years]:              | 5                            |
| Luminous efficacy [lm/W]:         | 116           | Manual:                        | <a href="#">Download PDF</a> |

Card creation date: 12 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr./2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl