

EXPO LED 3 MINI 1126LM 940 60° WHITE (9W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	837234
Rated power of the luminaire [W]*:	9
Ingress protection:	IP20
Luminous flux [lm]*:	1126
Colour temperature [K]:	4000
Color rendering index (Ra) >:	90
Electrical protection class:	I
Energy efficiency class:	D
Material of the body:	aluminium
Colour of the body:	white

CHARACTERISTICS

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

EXPO LED 3 MINI 1126LM 940 60° WHITE (9W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	837234	Optics:	reflector
EAN:	5905963837234	Material of the body:	aluminium
Light source:	LED	Colour of the body:	white
Rated power of the luminaire [W]:	9	Dimensions (H/W/T/S) [mm]:	86/185
Supply voltage [V]:	220 - 240	Ingress protection:	IP20
Luminous flux [lm]:	1126	Dimensions of single box [mm]:	285/122/122
Luminous efficacy [lm/W]:	125	Net weight [kg]:	0.810
Energy efficiency class:	D	Category type:	spotlight
Electrical protection class:	I	LED lifespan L90B10 [h]:	64000
Colour temperature [K]:	4000	Warranty [years]:	5
Color rendering index (Ra) >:	90	Manual:	Download PDF
Beam angle [°]:	60	Plik LDT:	Download
Optics material:	aluminium		

Card creation date: 12 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 109/2023