

# CONTRA LED SUSPENSION SYSTEM 1200X300

KARTA AKCESORIUM



## TECHNICAL PARAMETERS

**Index:** 374692

## CHARACTERISTICS

Contra LED versatile LED panel characterised by its low, slim profile and elegant design. Adapted for flush-mounted installation in modular ceilings, surface-mounted or suspended using an additional frame (available as an accessory). A luminaire with an integrated energy-saving LED module, made from a white painted aluminium profile, equipped with a structured multi-layer PS MAT or PRM lens for perfect light diffusion and low glare. It is used as a source of main light and is conducive to office work requiring visual focus or working with computer monitors (UGR  $\leq 19$  in versions with a prismatic diffuser).

## APPLICATION

The luminaire is intended for indoor use in office (offices, conference rooms) or representative use (hotels, restaurants); illumination of public facilities, including hospitals, educational facilities, offices, halls, garages, passageways, warehouses, shops, as well as in the food industry and food-related retail and service facilities. The unique design and excellent light performance enable CONTRA LED to be used as the main source of light, also for work that requires visual focus. The lamp is suitable for both new applications and the replacement of traditional T8 and T5 luminaires with energy-efficient LED solutions.

Card creation date: 30 June 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: