

# STRADO LED M 10825LM 740 RM7 IP66 II CL. DALI (69W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	411632
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK10
<b>Rated power of the luminaire [W]*:</b>	69
<b>Luminous flux [lm]*:</b>	10825
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	> 70
<b>Electrical protection class:</b>	II
<b>Optics:</b>	RM7
<b>Control:</b>	5-stage power reduction

## CHARACTERISTICS

STRADO LED is a new family of LED road luminaires. It uses directional multi-lens matrices, made of PMMA, with each lens having the same optics, ensuring that the luminous characteristics remain constant over time. Components from renowned manufacturers and state-of-the-art LED panels contribute to the very high luminous efficacy achieved at the output of the luminaire - reaching 165 lm/W. The upper part of the body has a separate electrical cavity in the body, which allows for efficient cooling of all power supply components, independently of the light module. The lower surface of the luminaire is finished entirely with toughened glass, providing high aesthetic qualities. The luminaire has an outgoing cable with a quick-release connector, which allows fast, convenient and reliable installation without opening the luminaire. Using standard tools, it is possible to service the luminaire, allowing any component to be replaced without soldering. The body and fixture are made of die-cast aluminium, powder-coated grey, and have a very high IP66 ingress protection rating and IK10 mechanical impact resistance. Standard features: fully programmable DALI driver; available functions for maintaining constant luminous flux during CLO and autonomous 5-step power reduction; NTC protection against accidental overheating of the luminaire; filter to prevent condensation; outgoing cable with quick-connector. Additional options: NEMA, ZHAGA connectors on the top of the luminaire; interfacing with control systems; additional SP10kV protection outside the power supply, on/off power supply without power reduction function; painting in any RAL colour. Certifications: CE, RoHS, ENEC, ENEC+, Zhaga D4i.

## APPLICATION

Thanks to the use of dedicated optics, it is possible to illuminate objects such as: highways, expressways, national, provincial, county, municipal, city, neighborhood, area lighting. Optics are also available to illuminate: pedestrian crossings, sidewalks and bicycle paths.

# STRADO LED M 10825LM 740 RM7 IP66 II CL. DALI (69W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	411632	<b>Material of the body:</b>	powder coated aluminium
<b>Rated power of the luminaire [W]:</b>	69	<b>Colour of the body:</b>	grey
<b>EAN:</b>	5905963411632	<b>Dimensions (H/W/T/S) [mm]:</b>	505/265/60
<b>Luminous flux [lm]:</b>	10825	<b>Mounting dimensions [mm]:</b>	ø60
<b>ETIM class:</b>	EC000062	<b>Impact resistance:</b>	IK10
<b>Luminous efficacy [lm/W]:</b>	157	<b>Ingress protection:</b>	IP66
<b>Category type:</b>	street lighting	<b>Mounting version:</b>	Top, on pole / Side, on boom
<b>Energy efficiency class:</b>	C	<b>Tilt angle adjustment [°]:</b>	-20° to +20°
<b>Version:</b>	M	<b>Lateral surface (SCx) [m2]:</b>	0.021
<b>Colour temperature [K]:</b>	4000	<b>Working temperature [°C]:</b>	from -40 to +50
<b>Light source:</b>	LED module	<b>LED lifespan L90B10 [h]:</b>	100000
<b>Colour rendering index:</b>	> 70	<b>Control:</b>	5-stage power reduction
<b>Electrical protection class:</b>	II	<b>Protection type:</b>	NTC + ESD
<b>Supply voltage [V]:</b>	220 - 240	<b>Net weight [kg]:</b>	4.450
<b>Optics:</b>	RM7	<b>ULOR:</b>	0%
<b>Frequency [Hz]:</b>	50 - 60	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>DIMM DALI:</b>	yes	<b>Technical Warranty:</b>	5 with the possibility of extension to 10
<b>SDCM:</b>	≤ 5	<b>Environmental Product Declaration (EPD):</b>	682/2024
<b>Surge protection [kV]:</b>	10	<b>ENEC Certificate:</b>	<a href="#">0390/ENEC/24; 0133/ENEC+/24</a>
<b>Diffuser material:</b>	toughened glass	<b>CE certificate:</b>	<a href="#">86/2023</a>
<b>Diffuser type:</b>	transparent	<b>Zhaga-D4i:</b>	<a href="#">ZG415027092023</a>
<b>Optics material:</b>	PMMA	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Exchangeable source:</b>	yes		

## LIGHT CURVES



# STRADO LED M 10825LM 740 RM7 IP66 II CL. DALI (69W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)



wall holder (galvanized) (314049)



wall holder (grey) (314056)

Card creation date: 21 November 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 86/2023