

EXPO LED 2 1126LM 38° WHITE 940 (9W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Rated power of the luminaire [W]*:	9
Luminous flux [lm]*:	1126
Colour temperature [K]:	4000
Colour rendering index:	90
Energy efficiency class:	D
Material of the body:	aluminium
Optics material:	aluminium

CHARACTERISTICS

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

EXPO LED 2 1126LM 38° WHITE 940 (9W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	750014	Optics:	reflector
EAN:	5905963750014	Material of the body:	aluminium
Light source:	LED	Colour of the body:	white
Rated power of the luminaire [W]:	9	Dimensions (H/W/T/S) [mm]:	107/225
Luminous flux [lm]:	1126	Ingress protection:	IP20
Luminous efficacy [lm/W]:	125	Net weight [kg]:	1.300
Energy efficiency class:	D	Warranty [years]:	5
Electrical protection class:	I	LED lifespan L90B10 [h]:	64000
Colour temperature [K]:	4000	Manual:	Download PDF
Colour rendering index:	90	Supply voltage [V]:	220 - 240
Beam angle [°]:	38°	Plik LDT:	Download
Optics material:	aluminium		

Card creation date: 07 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr:



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl