

# EXPO LED 2 1243LM 15° WHITE 830 (9W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP20
<b>Rated power of the luminaire [W]*:</b>	9
<b>Luminous flux [lm]*:</b>	1243
<b>Colour temperature [K]:</b>	3000
<b>Colour rendering index:</b>	>80
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	aluminium
<b>Optics material:</b>	aluminium

## CHARACTERISTICS

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

## APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

# EXPO LED 2 1243LM 15° WHITE 830 (9W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	9	Optics material:	aluminium
Index:	837807	Optics:	reflector
Colour temperature [K]:	3000	Material of the body:	aluminium
EAN:	5905963837807	Dimensions (H/W/T/S) [mm]:	107/225
Luminous flux [lm]:	1243	Ingress protection:	IP20
Light source:	LED	Net weight [kg]:	1.300
Beam angle [°]:	15°	Warranty [years]:	5
Colour of the body:	white	LED lifespan L90B10 [h]:	64000
Colour rendering index:	>80	Manual:	<a href="#">Download PDF</a>
Luminous efficacy [lm/W]:	138	Supply voltage [V]:	220 - 240
Energy efficiency class:	D	Plik LDT:	<a href="#">Download</a>
Electrical protection class:	I		

## LIGHT CURVES



Card creation date: 07 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr:



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl