

# EXPO LED 2 1297LM 38° WHITE 840 (9W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP20
<b>Rated power of the luminaire [W]*:</b>	9
<b>Luminous flux [lm]*:</b>	1297
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	>80
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	aluminium
<b>Optics material:</b>	aluminium

## CHARACTERISTICS

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

## APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

# EXPO LED 2 1297LM 38° WHITE 840 (9W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	837982	Optics material:	aluminium
EAN:	5905963837982	Optics:	reflector
Light source:	LED	Material of the body:	aluminium
Rated power of the luminaire [W]:	9	Colour of the body:	white
Luminous flux [lm]:	1297	Dimensions (H/W/T/S) [mm]:	107/225
Luminous efficacy [lm/W]:	144	Ingress protection:	IP20
Energy efficiency class:	D	Net weight [kg]:	1.300
Electrical protection class:	I	Warranty [years]:	5
Colour temperature [K]:	4000	LED lifespan L90B10 [h]:	64000
Colour rendering index:	>80	Manual:	<a href="#">Download PDF</a>
Beam angle [°]:	38°	Supply voltage [V]:	220 - 240

Card creation date: 07 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: