

EXPO LED 2 2950LM 60° WHITE 840 (22W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Rated power of the luminaire [W]*:	22
Luminous flux [lm]*:	2950
Colour temperature [K]:	4000
Colour rendering index:	80
Energy efficiency class:	D
Material of the body:	aluminium
Optics material:	aluminium

CHARACTERISTICS

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

EXPO LED 2 2950LM 60° WHITE 840 (22W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	750113	Optics:	reflector
EAN:	5905963750113	Material of the body:	aluminium
Light source:	LED	Colour of the body:	white
Rated power of the luminaire [W]:	22	Dimensions (H/W/T/S) [mm]:	107/225
Luminous flux [lm]:	2950	Ingress protection:	IP20
Luminous efficacy [lm/W]:	134	Net weight [kg]:	1.300
Energy efficiency class:	D	Warranty [years]:	5
Electrical protection class:	I	LED lifespan L90B10 [h]:	49000
Colour temperature [K]:	4000	Manual:	Download PDF
Colour rendering index:	80	Supply voltage [V]:	220 - 240
Beam angle [°]:	60°	Plik LDT:	Download
Optics material:	aluminium		