# EXPO LED 2 4053LM 15° WHITE 830 (35W)

**DETAILED CARD** 





## **TECHNICAL PARAMETERS**

Ingress protection: IP20

Rated power of the luminaire [W]\*: 35

Luminous flux [lm]\*: 4053

Colour temperature [K]: 3000

Colour rendering index: 80

Energy efficiency class:

Material of the body: aluminium

Optics material: aluminium

## **CHARACTERISTICS**

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

## **APPLICATION**

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.



## EXPO LED 2 4053LM 15° WHITE 830 (35W)

**DETAILED CARD** 

## **TECHNICAL PARAMETERS TABLE**

Index:	837821
EAN:	5905963837821
Light source:	LED
Rated power of the luminaire [W]:	35
Luminous flux [Im]:	4053
Luminous efficacy [lm/W]:	116
Energy efficiency class:	E
Electrical protection class:	1
Colour temperature [K]:	3000
Colour rendering index:	80
Beam angle [°]:	15°
Optics material:	aluminium

Optics:	reflector
Material of the body:	aluminium
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	107/225
Ingress protection:	IP20
Net weight [kg]:	1.300
Warranty [years]:	5
LED lifespan L90B10 [h]:	41000
Manual:	Download PDF
Supply voltage [V]:	220 - 240
Plik LDT:	Download

Card creation date: 07 July 2023



