

EXPO LED 2 4227LM 38° WHITE 840 (35W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Rated power of the luminaire [W]*:	35
Luminous flux [lm]*:	4227
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	E
Material of the body:	aluminium
Optics material:	aluminium

CHARACTERISTICS

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

EXPO LED 2 4227LM 38° WHITE 840 (35W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	35	Optics material:	aluminium
Index:	750007	Optics:	reflector
Colour temperature [K]:	4000	Material of the body:	aluminium
EAN:	5905963750007	Dimensions (H/W/T/S) [mm]:	107/225
Luminous flux [lm]:	4227	Ingress protection:	IP20
Light source:	LED	Net weight [kg]:	1.300
Beam angle [°]:	38°	Warranty [years]:	5
Colour of the body:	white	LED lifespan L90B10 [h]:	41000
Colour rendering index:	>80	Manual:	Download PDF
Luminous efficacy [lm/W]:	121	Supply voltage [V]:	220 - 240
Energy efficiency class:	E	Plik LDT:	
Electrical protection class:	I		

Card creation date: 07 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: