

# FLEX LINE LED 10M

DETAILED CARD



## TECHNICAL PARAMETERS

|                                    |           |
|------------------------------------|-----------|
| Light source:                      | LED       |
| Rated power of the luminaire [W]*: | 80        |
| Luminous flux [lm]*:               | 6633      |
| Supply voltage [V]:                | 220 - 240 |
| Frequency [Hz]:                    | 50        |
| Luminous efficacy [lm/W]:          | 83        |
| Energy efficiency class:           | F         |
| Electrical protection class:       | II        |
| Colour temperature [K]:            | 4000      |
| Colour rendering index:            | 70        |

## CHARACTERISTICS

The Flex Line LED light is a light line designed for quick and temporary illumination of a workstation or construction site. Available in 10m, 15m and 20m LED cable versions, it allows line connections of up to a maximum of 50m. The lamp's special shape and operating principle allows it to be freely mounted in a variety of working conditions (mounting on nails, screws, pipes, scaffolding, etc.) while directing the position of the light direction.

## APPLICATION

An innovative light chain designed for fast and versatile lighting of workplaces. Its unique shape and clever design, allow for express installation even in very unusual places: construction sites, workshops, renovations, vehicle repair areas, service shops, etc.

# FLEX LINE LED 10M

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|  |               |  |   |
|--|---------------|--|---|
| <b>Index:</b>                            | 608728        | <b>Ingress protection:</b>                     | IP44  |
| <b>EAN:</b>                              | 5905963608728 | <b>Plug type:</b>                              | UNI-SCHUKO  |
| <b>Light source:</b>                     | LED           | <b>Wire type:</b>                              | H07RN-F 2x1.5mm <sup>2</sup>  |
| <b>Rated power of the luminaire [W]:</b> | 80            | <b>Cable length [m]:</b>                       | 1.50  |
| <b>Luminous flux [lm]:</b>               | 6633          | <b>Dimensions of single box [mm]:</b>          | 273/278/98  |
| <b>Supply voltage [V]:</b>               | 220 - 240     | <b>Dimensions of bulk box (H/W/D) [mm]:</b>    | 565/285/520   |
| <b>Frequency [Hz]:</b>                   | 50            | <b>Number in carton box [pcs]:</b>             | 10  |
| <b>Luminous efficacy [lm/W]:</b>         | 83            | <b>Net weight [kg]:</b>                        | 1.580   |
| <b>Energy efficiency class:</b>          | F             | <b>Warranty [years]:</b>                       | 2   |
| <b>Electrical protection class:</b>      | II            | <b>Accessories included:</b>                   | Power cable 1.5M H07RN-F 2x1.5mm <sup>2</sup> with power supply and quick-connector |
| <b>Colour temperature [K]:</b>           | 4000          | <b>CE certificate:</b>                         | <a href="#">453/2023</a>  |
| <b>Colour rendering index:</b>           | 70            | <b>Manual:</b>                                 | <a href="#">Download PDF</a>  |
| <b>Colour of the body:</b>               | grey          | <b>Illumination area at a distance of 1 m:</b> | 2   |
| <b>Dimensions (H/W/T/S) [mm]:</b>        | 273/278/98    |  |   |

Card creation date: 27 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 453/2023