

FLEX LINE LED 15M

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED
Rated power of the luminaire [W]*:	120
Luminous flux [lm]*:	9950
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50
Luminous efficacy [lm/W]:	83
Energy efficiency class:	F
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	70

CHARACTERISTICS

The Flex Line LED light is a light line designed for quick and temporary illumination of a workstation or construction site. Available in 10m, 15m and 20m LED cable versions, it allows line connections of up to a maximum of 50m. The lamp's special shape and operating principle allows it to be freely mounted in a variety of working conditions (mounting on nails, screws, pipes, scaffolding, etc.) while directing the position of the light direction.

APPLICATION

An innovative light chain designed for fast and versatile lighting of workplaces. Its unique shape and clever design, allow for express installation even in very unusual places: construction sites, workshops, renovations, vehicle repair areas, service shops, etc.

FLEX LINE LED 15M

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	608735	Ingress protection:	IP44
EAN:	5905963608735	Plug type:	UNI-SCHUKO
Light source:	LED	Wire type:	H07RN-F 2x1.5mm ²
Rated power of the luminaire [W]:	120	Cable length [m]:	1.50
Luminous flux [lm]:	9950	Dimensions of single box [mm]:	273/278/98
Supply voltage [V]:	220 - 240	Dimensions of bulk box (H/W/D) [mm]:	565/285/420
Frequency [Hz]:	50	Number in carton box [pcs]:	8
Luminous efficacy [lm/W]:	83	Net weight [kg]:	2
Energy efficiency class:	F	Warranty [years]:	2
Electrical protection class:	II	Accessories included:	Power cable 1.5M H07RN-F 2x1.5mm ² with power supply and quick-connector
Colour temperature [K]:	4000	CE certificate:	453/2023
Color rendering index (Ra) >:	70	Manual:	Download PDF
Colour of the body:	grey	Illumination area at a distance of 1 m:	2
Dimensions (H/W/T/S) [mm]:	273/278/98		

Card creation date: 27 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 453/2023