

# FLEX LINE LED 15M

DETAILED CARD



## TECHNICAL PARAMETERS

Light source:	LED
Rated power of the luminaire [W]*:	120
Luminous flux [lm]*:	9950
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50
Luminous efficacy [lm/W]:	83
Energy efficiency class:	F
Electrical protection class:	II
Colour temperature [K]:	4000
Colour rendering index:	70

## CHARACTERISTICS

The Flex Line LED light is a light line designed for quick and temporary illumination of a workstation or construction site. Available in 10m, 15m and 20m LED cable versions, it allows line connections of up to a maximum of 50m. The lamp's special shape and operating principle allows it to be freely mounted in a variety of working conditions (mounting on nails, screws, pipes, scaffolding, etc.) while directing the position of the light direction.

## APPLICATION

An innovative light chain designed for fast and versatile lighting of workplaces. Its unique shape and clever design, allow for express installation even in very unusual places: construction sites, workshops, renovations, vehicle repair areas, service shops, etc.

# FLEX LINE LED 15M

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	608735	<b>Ingress protection:</b>	IP44
<b>EAN:</b>	5905963608735	<b>Plug type:</b>	UNI-SCHUKO
<b>Light source:</b>	LED	<b>Wire type:</b>	H07RN-F 2x1.5mm <sup>2</sup>
<b>Rated power of the luminaire [W]:</b>	120	<b>Cable length [m]:</b>	1.50
<b>Luminous flux [lm]:</b>	9950	<b>Dimensions of single box [mm]:</b>	273/278/98
<b>Supply voltage [V]:</b>	220 - 240	<b>Dimensions of bulk box (H/W/D) [mm]:</b>	565/285/420
<b>Frequency [Hz]:</b>	50	<b>Number in carton box [pcs]:</b>	8
<b>Luminous efficacy [lm/W]:</b>	83	<b>Net weight [kg]:</b>	2
<b>Energy efficiency class:</b>	F	<b>Warranty [years]:</b>	2
<b>Electrical protection class:</b>	II	<b>Accessories included:</b>	Power cable 1.5M H07RN-F 2x1.5mm <sup>2</sup> with power supply and quick-connector
<b>Colour temperature [K]:</b>	4000	<b>CE certificate:</b>	<a href="#">453/2023</a>
<b>Colour rendering index:</b>	70	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Colour of the body:</b>	grey	<b>Illumination area at a distance of 1 m:</b>	2
<b>Dimensions (H/W/T/S) [mm]:</b>	273/278/98		

Card creation date: 27 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 453/2023