

# TIARA 2 LED M 1250LM 740 RM7 IP66 II CL. DALI (8W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	915352
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK09
<b>Rated power of the luminaire [W]*:</b>	8
<b>Luminous flux [lm]*:</b>	1250
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	> 70
<b>Electrical protection class:</b>	II
<b>Optics:</b>	RM7

## CHARACTERISTICS

TIARA 2 LED a new generation of LED road luminaires. It uses directional multi-lens arrays made of PMMA, with each lens having the same optics, ensuring that the light characteristics remain constant over time. The luminaire's dual-chamber design maintains the integrity of the optical chamber during installation work and the opening of the electrical chamber. As standard, the luminaire offers tool-free access to the electrical fixtures using two independent clips, which, if desired and needed to protect against vandalism or uncontrolled opening, can optionally be permanently secured with screws or a seal. The upper part of the luminaire, has dedicated hinges and a safety cable to prevent falling. Using standard tools, quick and convenient service is possible, allowing replacement of any component without the need to disassemble the entire fixture and make soldered connections. The body and handle made of die-cast aluminum, powder-coated in gray, is characterized by a very high degree of IP66 and IK09 impact resistance. Standard features: ergonomic light module suspension system; NTC luminaire accidental overheating protection; fully programmable DALI driver; available functions for maintaining constant lumen output during CLO and autonomous 5-stage power reduction; filter to prevent condensation; connection terminals; tool-free access. Additional options: NEMA, ZHAGA connectors; interfacing with control systems, RCR motion sensor; anti-vandal protection with screws/seal; additional SP10kV protection outside the power supply, on/off power supply without power reduction function; knife disconnect switch that disconnects voltage if the electrical compartment is opened; design with cable terminated with quick disconnect; painting in any RAL color. Certifications: CE, RoHS, ENEC, ENEC+, Zhaga D4i.

## APPLICATION

Thanks to the use of dedicated optics, it is possible to illuminate objects such as: highways, expressways, national, provincial, county, municipal, city, neighborhood, area lighting. Optics are also available to illuminate: pedestrian crossings, sidewalks and bicycle paths.


# TIARA 2 LED M 1250LM 740 RM7 IP66 II CL. DALI (8W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	915352	<b>Material of the body:</b>	powder coated aluminium
<b>EAN:</b>	5905963915352	<b>Colour of the body:</b>	grey
<b>ETIM class:</b>	EC000062	<b>Dimensions (H/W/T/S) [mm]:</b>	597/265/105
<b>Category type:</b>	street lighting	<b>Mounting dimensions [mm]:</b>	ø60
<b>Version:</b>	M	<b>Impact resistance:</b>	IK09
<b>Light source:</b>	LED module	<b>Ingress protection:</b>	IP66
<b>Rated power of the luminaire [W]:</b>	8	<b>Mounting version:</b>	Top, on pole / Side, on boom
<b>Supply voltage [V]:</b>	220 - 240	<b>Beam angle adjustment [°]:</b>	-30° to +120° (peak); -120° to +30° (side)
<b>Frequency [Hz]:</b>	50 - 60	<b>Lateral surface (SCx) [m2]:</b>	0.028
<b>Luminous flux [lm]:</b>	1250	<b>Working temperature [°C]:</b>	from -40 to +50
<b>Luminous efficacy [lm/W]:</b>	156	<b>LED lifespan L90B10 [h]:</b>	100000
<b>Energy efficiency class:</b>	C	<b>DIMM DALI:</b>	yes
<b>Electrical protection class:</b>	II	<b>Control:</b>	Yes + 5-stage power reduction
<b>Colour temperature [K]:</b>	4000	<b>Protection type:</b>	NTC
<b>Colour rendering index:</b>	> 70	<b>Vandalproof:</b>	yes
<b>SDCM:</b>	≤ 5	<b>Net weight [kg]:</b>	5.200
<b>Power factor:</b>	0.93	<b>Technical Warranty:</b>	5 with the possibility of extension to 10
<b>Surge protection [kV]:</b>	10	<b>ULOR:</b>	0%
<b>Diffuser material:</b>	toughened glass	<b>ENEC Certificate:</b>	<a href="#">0356/ENEC/24; 0120/ENEC+/24</a>
<b>Diffuser type:</b>	transparent	<b>CE certificate:</b>	<a href="#">07/2024</a>
<b>Optics material:</b>	PMMA	<b>Zhaga-D4i:</b>	<a href="#">ZG407120042023</a>
<b>Optics:</b>	RM7	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Exchangeable source:</b>	yes		

## LIGHT CURVES



# TIARA 2 LED M 1250LM 740 RM7 IP66 II CL. DALI (8W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
UL01350	Handle fi 76mm for Tiara 2 LED M and Tiara 2 LED S



wall holder (galvanized) (314049)



wall holder (grey) (314056)

Card creation date: 20 May 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 07/2024