

SQ 600 LED IOT BT RCR HYT 2900LM PLX I CL. 592X592MM 830 (29W)

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Nominal power [W]:	29
Luminous flux [lm]*:	2900
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	88
Energy efficiency class:	F
Electrical protection class:	I
Colour temperature [K]:	3000
Diffuser colour:	white

CHARACTERISTICS

The SQ 600 LED IoT is a new line of square raster lights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic for low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Ensures low power consumption and all the advantages of modern LED lamps. Degree of protection - dependent on mounting method: - surface-mounted - IP20, - recessed - IP44/20.**IoT characteristics**The **IoT BT RCR HYT** version has: a built-in **BT HYT** module allowing for programming functions in the Lena Lighting Clue app and real-time control; **RCR** motion and daylight sensor hidden under the shade and **ON/OFF** driver without dimming function of the light source.

APPLICATION

Surface-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.


SQ 600 LED IOT BT RCR HYT 2900LM PLX I CL. 592X592MM 830 (29W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	670862	Diffuser colour:	white
Light source:	LED module	Optics:	lens
Nominal power [W]:	29	Optics material:	PMMA
Luminous flux [lm]:	2900	Material of the body:	ABS
Supply voltage [V]:	220-240	Colour of the body:	white
Frequency [Hz]:	50-60	Dimensions (H/W/T/S) [mm]:	592/592/44
Luminous efficacy [lm/W]:	88	Ingress protection:	IP44/IP20
Energy efficiency class:	F	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Electrical protection class:	I	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Colour temperature [K]:	3000	Motion sensor:	yes
Color rendering index (Ra) >:	80	Category type:	troffers
LED lifespan L70B50 [h]:	50000	Photobiological safety:	RG0 - exempt (no photobiological hazard)
LED lifespan L80B10 [h]:	32000	Warranty [years]:	5
LED lifespan L90B10 [h]:	15000	CE certificate:	442/2023
Beam angle [°]:	120	PZH certificate:	B-BK-60112-0419/2025
Light distribution type:	open space	Environmental Product Declaration (EPD):	944/2026
Diffuser material:	PS	Manual:	Download PDF
Diffuser type:	OPAL	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018

LIGHT CURVES



SQ 600 LED IOT BT RCR HYT 2900LM PLX I CL. 592X592MM 830 (29W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
978395	Installation kit SQ 600 Ceiling system H40 100x100
374845	Frame adapter KG 635x635 WHITE



Frame adapter KG 635x635
WHITE (374845)

Card creation date: 04 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 442/2023