

SQ 600 LED IOT BT HYT DALI 3700LM PLX I CL. 592X592MM 840 (37W)

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Nominal power [W]:	37
Luminous flux [lm]*:	3700
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	87
Energy efficiency class:	F
Electrical protection class:	I
Colour temperature [K]:	4000
Diffuser colour:	white

CHARACTERISTICS

The SQ 600 LED IoT is a new line of square raster lights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic for low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Ensures low power consumption and all the advantages of modern LED lamps. Degree of protection - dependent on mounting method: - surface-mounted - IP20, - recessed - IP44/20.**IoT characteristics**The **IoT BT HYT DALI** version has: a built-in **BT HYT** module that allows you to program functions in the Lena Lighting Clue app and control in real time, and a **DALI** driver that allows you to dim the light source.

APPLICATION

Surface-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.


SQ 600 LED IOT BT HYT DALI 3700LM PLX I CL. 592X592MM 840 (37W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	670701	Optics:	lens
Light source:	LED module	Optics material:	PMMA
Nominal power [W]:	37	Material of the body:	ABS
Luminous flux [lm]:	3700	Colour of the body:	white
Supply voltage [V]:	220-240	Dimensions (H/W/T/S) [mm]:	592/592/44
Frequency [Hz]:	50-60	Ingress protection:	IP44/IP20
Luminous efficacy [lm/W]:	87	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Energy efficiency class:	F	Version:	BT HYT DALI
Electrical protection class:	I	DIMM DALI:	yes
Colour temperature [K]:	4000	Warranty [years]:	5
Colour rendering index:	>80	Category type:	louvres
LED lifespan L70B50 [h]:	50000	CE certificate:	442/2023
LED lifespan L80B20 [h]:	32000	ENEC Certificate:	
LED lifespan L90B10 [h]:	15000	PZH certificate:	
Beam angle [°]:	120	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Light distribution type:	open space		
Diffuser material:	PS		
Diffuser type:	OPAL		
Diffuser colour:	white		

LIGHT CURVES



SQ 600 LED IOT BT HYT DALI 3700LM PLX I CL. 592X592MM 840 (37W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
978395	Installation kit SQ 600 Ceiling system H40 100x100



Plasterboard recessing kit 630x630
white (steel version) (999543)

Card creation date: 10 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 442/2023