

# SQ 600 LED IOT BT RCR HYT 3500LM PLX I CL. 592X592MM 830 (37W)

DETAILED CARD



## TECHNICAL PARAMETERS

Light source:	LED module
Nominal power [W]:	37
Luminous flux [lm]*:	3500
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	83
Energy efficiency class:	F
Electrical protection class:	I
Colour temperature [K]:	3000
Diffuser colour:	white

## CHARACTERISTICS

The SQ 600 LED IoT is a new line of square raster lights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic for low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Ensures low power consumption and all the advantages of modern LED lamps. Degree of protection - dependent on mounting method: - surface-mounted - IP20, - recessed - IP44/20.**IoT characteristics**The **IoT BT RCR HYT** version has: a built-in **BT HYT** module allowing for programming functions in the Lena Lighting Clue app and real-time control; **RCR** motion and daylight sensor hidden under the shade and **ON/OFF** driver without dimming function of the light source.

## APPLICATION

Surface-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.


# SQ 600 LED IOT BT RCR HYT 3500LM PLX I CL. 592X592MM 830 (37W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	670909	<b>Optics:</b>	lens
<b>Light source:</b>	LED module	<b>Optics material:</b>	PMMA
<b>Nominal power [W]:</b>	37	<b>Material of the body:</b>	ABS
<b>Luminous flux [lm]:</b>	3500	<b>Colour of the body:</b>	white
<b>Supply voltage [V]:</b>	220-240	<b>Dimensions (H/W/T/S) [mm]:</b>	592/592/44
<b>Frequency [Hz]:</b>	50-60	<b>Ingress protection:</b>	IP44/IP20
<b>Luminous efficacy [lm/W]:</b>	83	<b>Mounting version:</b>	surface mounted; recessed mounted in modular ceiling possible
<b>Energy efficiency class:</b>	F	<b>Version:</b>	BT RCR HYT
<b>Electrical protection class:</b>	I	<b>Motion sensor:</b>	yes
<b>Colour temperature [K]:</b>	3000	<b>Warranty [years]:</b>	5
<b>Colour rendering index:</b>	>80	<b>Category type:</b>	louvres
<b>LED lifespan L70B50 [h]:</b>	50000	<b>CE certificate:</b>	<a href="#">442/2023</a>
<b>LED lifespan L80B20 [h]:</b>	32000	<b>ENEC Certificate:</b>	
<b>LED lifespan L90B10 [h]:</b>	15000	<b>PZH certificate:</b>	
<b>Beam angle [°]:</b>	120	<b>Photobiological safety:</b>	RG0 - exempt (no photobiological hazard)
<b>Light distribution type:</b>	open space		
<b>Diffuser material:</b>	PS		
<b>Diffuser type:</b>	OPAL		
<b>Diffuser colour:</b>	white		

## LIGHT CURVES



# SQ 600 LED IOT BT RCR HYT 3500LM PLX I CL. 592X592MM 830 (37W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
978395	Installation kit SQ 600 Ceiling system H40 100x100



Plasterboard recessing kit 630x630  
white (steel version) (999543)

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 442/2023