

# INDO LED EVO P DALI 3700LM PLX 840 (34W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	380938
<b>Ingress protection:</b>	IP20
<b>Nominal power [W]:</b>	34
<b>Luminous flux [lm]*:</b>	3700
<b>Colour temperature [K]:</b>	4000
<b>SDCM:</b>	3
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	powder coated steel
<b>Diffuser material:</b>	PMMA
<b>Diffuser type:</b>	OPAL

## CHARACTERISTICS

Recessed mounted square luminaire with an integrated energy-saving LED light source. Powder-coated steel body. The lens diffuser is made of metal sheet and opalized PMMA. It provides comfortable and soft light.

## APPLICATION

A versatile indoor luminaire designed for office rooms and areas of general public use. Suitable as a general light source for all sorts of work that require optical focus. Dedicated for new applications and as a replacement of traditional T8 and T5 tube luminaires with energy-saving LED lamps


# INDO LED EVO P DALI 3700LM PLX 840 (34W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	380938	Material of the body:	powder coated steel
Light source:	LED module	Colour of the body:	white
Nominal power [W]:	34	Dimensions (H/W/T/S) [mm]:	106/595/595
Rated power of the luminaire [W]:	36.80	Impact resistance:	IK07
Supply voltage [V]:	220-240	Ingress protection:	IP20
Frequency [Hz]:	50 - 60	Mounting version:	recessed
Luminous flux [lm]:	3700	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	100	EAN:	5905963380938
Energy efficiency class:	E	Category type:	troffers
Electrical protection class:	I	AC voltage range [V]:	198 – 264
Colour temperature [K]:	4000	ETIM class:	EC002892
Color rendering index (Ra) >:	80	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
SDCM:	3	Warranty [years]:	5
Power factor:	0.96	Manual:	<a href="#">Download PDF</a>
LED lifespan L70B50 [h]:	50 000	DIMM DALI:	yes
Diffuser material:	PMMA	CE certificate:	<a href="#">77/2018</a>
Diffuser type:	OPAL	Plik LDT:	<a href="#">Download</a>

## LIGHT CURVES



# INDO LED EVO P DALI 3700LM PLX 840 (34W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
374845	Frame adapter KG 635x635 WHITE



Frame adapter KG 635x635  
WHITE (374845)

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 77/2018