TERRA 3 LED P 1195X295MM X4 6000LM 840 WHITE GLOSS (40W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:418662Rated power of the luminaire [W]*:40Luminous flux [Im]*:6000Colour temperature [K]:4000Color rendering index (Ra) >:80

Material of the body:powder coated steelColour of the body:white glossDimensions (H/W/T/S) [mm]:1195/295/32Mounting version:recessedEnergy efficiency class:C

CHARACTERISTICS

A luminaire equipped with energy-efficient LED modules characterised by high luminous flux. The low side profile provides an aesthetically pleasing, timeless appearance. Robust, compact construction. Made of powder-coated steel sheet. Patented high-performance HE reflector guarantees high efficiency while effectively eliminating glare.

APPLICATION

The versatile luminaire is designed for indoor use in offices or general utility rooms. Its high luminous parameters make it suitable as the main source of light and conducive to work requiring visual focus. The luminaire is suitable for both new applications and the replacement of traditional fluorescent lamps with energy-efficient LED solutions.



TERRA 3 LED P 1195X295MM X4 6000LM 840 WHITE GLOSS (40W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index: 418662
EAN: 5905963418662
Light source: LED
Rated power of the luminaire [W]: 40
Luminous flux [lm]: 6000
Luminous efficacy [lm/W]: 150
Ingress protection: IP20
Energy efficiency class: C
Electrical protection class:
Colour temperature [K]: 4000
Color rendering index (Ra) >: 80
Beam angle [°]: 60
Diffuser material: PC
Diffuser type: matrix led
Diffuser colour: transparent
Optics material: PC

Material of the body:	powder coated steel
Colour of the body:	white gloss
Dimensions (H/W/T/S) [mm]:	1195/295/32
Mounting version:	recessed
Number on the palette [pcs]:	60
Net weight [kg]:	1.930
Category type:	troffers
Version:	4x1
Light distribution type:	symmetric
LED lifespan L70B50 [h]:	150000
LED lifespan L80B20 [h]:	100000
LED lifespan L90B10 [h]:	50000
Warranty [years]:	5
CE certificate:	60/2025
Manual:	Download PDF
Plik LDT:	Download





TERRA 3 LED P 1195X295MM X4 6000LM 840 WHITE GLOSS (40W)


DETAILED CARD

ACCESSORIES AVAILABLE

 index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"







Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 27 October 2025



