

COLLINE X TERRANO H60.120 3200LM 840 II CL. BLACK 60D (28W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	414664
EAN:	5905963414664
Light source:	LED module
Rated power of the luminaire [W]*:	28
Luminous flux [lm]*:	3200
Luminous efficacy [lm/W]:	115
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	4000

CHARACTERISTICS

Acoustic lamps created by Lena Lighting and Acustio. They provide, in addition to a spectacular design effect, glare-free lighting that is friendly to the senses (UGR ranges from 12 - 19) and sound attenuation at the level of high-class sound absorption. The luminaire is made of a triple layer of felt, which makes it durable while maintaining its softness. In addition, it can be coated with a layer of nano-silver in accordance with Acustio's proprietary brand technology - NanoFelt Ag. It provides high protection against the deposition of bacterial particles on the surface. Lighting, on the other hand, is based on energy-saving LED modules that emit light in two colors 4000K or 3000K (on request). It is also available with DALI control, allowing the light output to be adjusted to outdoor conditions, and compatibility with Lena Lighting's proprietary Clue control system. It allows you to set light scenes, dim lamps or program individual light output settings for individual lamps and group them together - all from an app on your phone or from the control panel. The modular design of Colline x Terrano, a choice of different acoustic panel embossings and a wide range of colors provide unlimited personalization possibilities.

APPLICATION

Spaces conducive to both work and relaxation. They will work well in both offices and private homes, creating a friendly place for remote work, rest, sleep and entertainment.

DETAILS

COLLINE X TERRANO H60.120 3200LM 840 II CL. BLACK 60D (28W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	414664	Category of application:	architectural
EAN:	5905963414664	Supply voltage [V]:	220 - 240
Rated power of the luminaire [W]:	28	AC voltage range [V]:	198-264
Light source:	LED module	Frequency [Hz]:	50-60
Luminous flux [lm]:	3200	SDCM:	≤ 3
Luminous efficacy [lm/W]:	115	Power factor:	0.93
Energy efficiency class:	D	ITHD [%]:	15
Colour temperature [K]:	4000	Flicker procent:	5
Electrical protection class:	II	Diffuser material:	PC
Version:	H60.120	Diffuser type:	matrix led
Colour rendering index:	>80	Diffuser colour:	transparent
Beam angle [°]:	60	Working temperature [°C]:	from -10 to +35
Light distribution type:	symmetric	Diode PCB material:	aluminium
Optics:	lens	Diode size [mm]:	3030
Optics material:	PC	Number on the palette [pcs]:	8
Dimensions (H/W/T/S) [mm]:	598/38/1115	Net weight [kg]:	2.900
Ingress protection:	IP20	Warranty [years]:	5
Colour of the body:	black	CE certificate:	464/2023
Category type:	architectural	Manual:	Download PDF
		Plik LDT:	

Card creation date: 31 August 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 464/2023