


# COLLINE X TERRANO H60.120 4400LM 840 II CL. BLACK 60D (40W)

DETAILED CARD



## TECHNICAL PARAMETERS

|   |               |
|---|---------------|
| <b>Index:</b>                             | 414688        |
| <b>EAN:</b>                               | 5905963414688 |
| <b>Light source:</b>                      | LED module    |
| <b>Rated power of the luminaire [W]*:</b> | 40            |
| <b>Luminous flux [lm]*:</b>               | 4400          |
| <b>Luminous efficacy [lm/W]:</b>          | 110           |
| <b>Energy efficiency class:</b>           | E             |
| <b>Electrical protection class:</b>       | II            |
| <b>Colour temperature [K]:</b>            | 4000          |

## CHARACTERISTICS

Acoustic lamps created by Lena Lighting and Acustio. They provide, in addition to a spectacular design effect, glare-free lighting that is friendly to the senses (UGR ranges from 12 - 19) and sound attenuation at the level of high-class sound absorption. The luminaire is made of a triple layer of felt, which makes it durable while maintaining its softness. In addition, it can be coated with a layer of nano-silver in accordance with Acustio's proprietary brand technology - NanoFelt Ag. It provides high protection against the deposition of bacterial particles on the surface. Lighting, on the other hand, is based on energy-saving LED modules that emit light in two colors 4000K or 3000K (on request). It is also available with DALI control, allowing the light output to be adjusted to outdoor conditions, and compatibility with Lena Lighting's proprietary Clue control system. It allows you to set light scenes, dim lamps or program individual light output settings for individual lamps and group them together - all from an app on your phone or from the control panel. The modular design of Colline x Terrano, a choice of different acoustic panel embossings and a wide range of colors provide unlimited personalization possibilities.

## APPLICATION

Spaces conducive to both work and relaxation. They will work well in both offices and private homes, creating a friendly place for remote work, rest, sleep and entertainment.

## DETAILS


# COLLINE X TERRANO H60.120 4400LM 840 II CL. BLACK 60D (40W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |               |                              |                              |
|-----------------------------------|---------------|------------------------------|------------------------------|
| Index:                            | 414688        | Category of application:     | architectural                |
| EAN:                              | 5905963414688 | SDCM:                        | ≤ 3                          |
| Rated power of the luminaire [W]: | 40            | Power factor:                | 0.90                         |
| Light source:                     | LED module    | ITHD [%]:                    | 15                           |
| Luminous flux [lm]:               | 4400          | Flicker procent:             | 30                           |
| Luminous efficacy [lm/W]:         | 110           | Diffuser material:           | PC                           |
| Energy efficiency class:          | E             | Diffuser type:               | matrix led                   |
| Colour temperature [K]:           | 4000          | Diffuser colour:             | transparent                  |
| Electrical protection class:      | II            | Working temperature [°C]:    | from -10 to +35              |
| Version:                          | H60.120       | Diode PCB material:          | aluminium                    |
| Colour rendering index:           | >80           | Diode size [mm]:             | 3030                         |
| Beam angle [°]:                   | 60            | Number on the palette [pcs]: | 8                            |
| Light distribution type:          | symmetric     | Net weight [kg]:             | 2.900                        |
| Optics:                           | lens          | LED lifespan L70B50 [h]:     | 156000                       |
| Optics material:                  | PC            | LED lifespan L80B20 [h]:     | 98000                        |
| Dimensions (H/W/T/S) [mm]:        | 598/38/1115   | LED lifespan L90B10 [h]:     | 47000                        |
| Ingress protection:               | IP20          | Warranty [years]:            | 5                            |
| Colour of the body:               | black         | CE certificate:              | <a href="#">464/2023</a>     |
| Category type:                    | architectural | Manual:                      | <a href="#">Download PDF</a> |
|                                   |               | Pliik LDT:                   | <a href="#">Download</a>     |

## LIGHT CURVES



Card creation date: 31 August 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 464/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl