

TIUNNE PLUS 200 2700LM 830 15D WHITE IP65/IP20 REFLECTOR W 28W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	425745
Ingress protection:	IP65/IP20
Rated power of the luminaire [W]*:	28
Luminous flux [lm]*:	2700
Colour temperature [K]:	3000
Colour rendering index:	>80
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	white
Diffuser material:	PC

CHARACTERISTICS

Tiunne Plus is a decorative downlight luminaire for installation in suspended ceilings. It is energy-efficient and durable thanks to the COB LED light source used. It has a classic circular shape that blends in with any type of space. It is available in several versions with different light distribution angles and four reflector colours.

The lamp housing designed in aluminium ensures optimum working conditions for the LEDs, and the aluminium reflector guarantees high luminous efficiency and low glare - features that distinguish the best LED downlight luminaires. The luminaire is suitable for installation in plasterboard and modular ceilings. Colour temperature 3000K, 4000K; CRI>80, CRI>90.

APPLICATION

The luminaire is designed for indoor use as general lighting. It is ideal for walkways, entrance areas, shop windows and fitting rooms in commercial premises.

DETAILS

LED lifespan: L70F50 >60 000h; L80F10 >60 000h; L90F10 57 000h

TIUNNE PLUS 200 2700LM 830 15D WHITE IP65/IP20 REFLECTOR W 28W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	425745	Optics material:	aluminium
EAN:	5905963425745	Optics:	reflector W
Light source:	COB	Material of the body:	aluminium
Rated power of the luminaire [W]:	28	Colour of the body:	white
Luminous flux [lm]:	2700	Ring material:	aluminium
Remarks:	W- white matt	Ring colour:	white
Luminous efficacy [lm/W]:	97	Dimensions (H/W/T/S) [mm]:	ø215/110
Energy efficiency class:	E	Mounting dimensions [mm]:	200
Electrical protection class:	II	Ingress protection:	IP65/IP20
Colour temperature [K]:	3000	Mounting version:	recessed
Colour rendering index:	>80	Working temperature [°C]:	35
SDCM:	3	Net weight [kg]:	0.550
Beam angle [°]:	15	Category type:	downlights
Surge protection [kV]:	1	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	469/2023
Diffuser type:	transparent	Manual:	Download PDF

LIGHT CURVES



Card creation date: 23 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 469/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl